

## LD35TT3

Thermal Transfer Label, 3.0" X 5.0", Paper, White, 1300/RL

Article Number: 596-00335

Part Number: LD35TT3

Type: LD35TT3

[→ Find a Distributor](#)

[→ Order Samples](#)

[→ Get Technical Drawings](#)



- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▶ [Heavy Duty Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
- ▶ [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

### → Base Data

<b>Part No.</b>	LD35TT3
<b>Type</b>	LD35TT3
<b>Color</b>	White (WH)
<b>Features</b>	<ul style="list-style-type: none"> <li>HellermannTyton Thermal Transfer Paper labels are ideal for temporary applications due to low cost.</li> <li>The labels come in the most common sizes to fit most packaging applications.</li> </ul>
<b>Application Method</b>	Labels are printed using a HellermannTyton thermal transfer printer and then applied by hand.

### → Product Dimensions

<b>Length (L)</b>	5.0" / 127.0mm
<b>Width (W) (imperial)</b>	3.0"
<b>Width (W)</b>	76.2mm
<b>Height (H)</b>	5.0" / 127.0mm
<b>Print Method</b>	Thermal Transfer

### → Material and Specifications

<b>Material</b>	Paper (PAP)
<b>Operating Temperature</b>	-40 °F to +180 °F (-40 °C to +82 °C)
<b>ROHS Conformity</b>	RoHS

### → Logistic and Packaging

<b>Packaging Type</b>	case
<b>Pkg. Qty.</b>	1 / 1
<b>UPC</b>	089306279150

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)