



NOTE 1. NO PLATING ON THE SHEARED EDGES OF CONTACT.
 NOTE 2. CRIMP TYPE ARE MARKED AS INDICATED.

TABLE 1

| CRIMP TYPE | APPLICABLE WIRE | | DIMENSIONS | | | |
|------------|--------------------------|--------------------------|------------|------|------|------|
| | WIRE SIZE | INSULATION OUTER DIA. | A | B | C | D |
| C 1 | AWG#18~22 (0.8mm~0.3mm) | $\phi 2.3$ MAX. | 28.43 | 5.81 | 3.92 | 2.49 |
| C 2 | AWG#22~26 (0.3mm~0.13mm) | $\phi 1.0 \sim \phi 1.7$ | 29.04 | 6.42 | 4.53 | 2.7 |

| | | | | | | | | |
|-----------------------------------------------------------|----------------|--------------|-------------------------------------------------------------------------------------------------|----------------|------------|--------------------------------------------|--|--|
| 1 | #20PIN CONTACT | 1 | COPPER ALLOY | SILVER PLATING | | | | |
| ITEM | DESCRIPTION | Q'TY | MATERIAL | FINISH | REMARKS | | | |
| UNLESS OTHERWISE SPECIFIED: T700142 | | DATE | TITLE | | | | | |
| DIMENSIONS ARE IN MILLIMETERS TOLERANCES ON : (INCHES) | | 13. Mar. '95 | JAE-CONNECTOR.COM Reference Only ST-JL05-20P-C (#20PIN CONTACT) (INDIVIDUAL) | | | | | |
| | | DRAWN | | | | JAPAN INJECTION ELECTRONICS INDUSTRY, LTD. | | |
| | | S. NANA O | | | | MUSASHINO, AKISHIMA-SHI | | |
| | | CHECKED | | | | TOKYO, JAPAN | | |
| FRACTIONS | | APP'D | SCALE | | DWG. NO. | | | |
| DECIMALS | | M. Takagi | 3/1 | | SJ025420-E | | | |
| ANGLES | | APP'D | SERIES | | | | | |
| | | | JL05 | | | | | |