

Han Q 8/0-gg-PG21



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 008 0429
Specification	Han Q 8/0-gg-PG21
HARTING eCatalogue	https://b2b.harting.com/09120080429

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Compact [®]
Type of hood/housing	Hood
Description of hood/housing	for Han-Compact [®] half cable gland

Version

Size	Han-Compact [®]
Version	Top entry
Cable entry	1x Pg 21
Locking type	Single locking lever
Field of application	Hoods/housings for industrial applications

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0



Pushing Performance
Since 1945

Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	10
Net weight	22.34 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140017627
eCl@ss	27440202 Shell for industrial connectors