

10		9		8		7		6		5		4		3		2		1				
AMPS		TYPE		DIMENSIONS:																		
				("A")	("B")	("C")	("D")	("E")	("F")	("G")	("H")											
20		3 WIRE		2.82 [71.5]	2.05 [52.0]	1.10 [28.0]	1.81 [46.0]	2.44 [62.0]	2.44 [62.0]	1.85 [47.0]	1.85 [47.0]											
20		4 WIRE		3.19 [81.0]	2.05 [52.0]	1.10 [28.0]	2.36 [60.0]	2.95 [75.0]	2.95 [75.0]	2.36 [60.0]	2.36 [60.0]											
30		3 & 4 WIRE		3.78 [96.0]	2.56 [65.0]	1.06 [27.0]	2.36 [60.0]	2.95 [75.0]	2.95 [75.0]	2.36 [60.0]	2.36 [60.0]											
60		3,4 & 5 WIRE		4.29 [109.0]	3.27 [83.0]	2.05 [52.0]	3.54 [90.0]	3.94 [100.0]	4.21 [107.0]	3.03 [77.0]	3.35 [85.0]											
100		3,4 & 5 WIRE		5.12 [130.0]	3.78 [96.0]	2.52 [64.0]	3.54 [90.0]	4.49 [114.0]	4.49 [114.0]	3.54 [90.0]	3.54 [90.0]											
NOTES:																						
1. THE BELOW WATERTIGHT PIN AND SLEEVE RECPT. ARE RATED : IP67.																						
POLE/WIRE		AMPS	VOLTAGE	MATERIAL No.	ENGINEERING No.	COLOR																
2-Pole/3-Wire		20	125	1301500057	320R4W	Yellow																
			250	1301500059	320R6W	Blue																
3-Pole/4-Wire			125/250	1301500144	420R12W	Orange																
			3ø250	1301500150	420R9W	Blue																
			3ø480	1301500148	420R7W	Red																
3-Pole/4-Wire		30	3ø600	1301500146	420R5W	Black																
			3-Pole/4-Wire		60	3ø250	1301500179	430R9W	Blue													
						3ø480	1301500177	430R7W	Red													
3ø600	1301500175	430R5W				Black																
3-Pole/4-Wire		100	125/250	1301500207	460R12W	Orange																
			3ø250	1301500213	460R9W	Blue																
			3ø480	1301500211	460R7W	Red																
3-Pole/4-Wire		100	3ø600	1301500209	460R5W	Black																
			125/250	1301500116	4100R12W	Orange																
			3ø250	1301500119	4100R9W	Blue																
3-Pole/4-Wire		100	3ø480	1301500118	4100R7W	Red																
			3ø600	1301500117	4100R5W	Black																
DOCUMENT STATUS		P1	RELEASE DATE	2021/05/05	21:55:30																	