



- \* MATERIAL : HIGH IMPACT OF UL94-HB ABS
- \* ORDER BY PART NUMBER BELOW, LIGHT GREY OR BLACK COLOR:  
 PTH - 11810 - G: GREY  
 PTH - 11810 - B: BLACK
- \* FINISH:  
 BASE: SMOOTH  
 LID: TEXTURED WITH SMOOTH RECESSED AREA.
- \* SNAP-IN DESIGN CAN BE OPENED AND CLOSED EASILY WITHOUT A TOOL
- \* CABLE ENTRY RUBBER CAN BE CUT EASILY WITH A KNIFE FOR CABLE CONNECTION
- \* 4 INTERNAL BOSSES ARE AVAILABLE FOR PCB ASSEMBLY. USE M2.5 OR #4 STD SHEET METAL SCREWS.
- \* IDEALLY USED FOR INDOOR/OUTDOOR TELECOMMUNICATION DEVICE.
- \* ALL DIMENSIONAL TOLERANCES ARE .015

TOLERANCES:		ITEM REQ'D	PART NO.	DESCRIPTION
±.005 BETWEEN HOLE CENTERS	AS NOTED			NAME:
±.015 FROM SHEARED EDGE	FINISH: NOTED			BUD
±.032 FROM A BENT SURFACE	DR. RD 10-13-08			BUD INDUSTRIES, INC
±.063 BETWEEN ASSEMBLED SURFACES	CH.			WILLOUGHBY, OHIO
UNLESS OTHERWISE SPECIFIED	APP.			DWG. NO. PTH-11810