





MALE PLUG M12 STRAIGHT



NOTES:
RATED VOLTAGE: 3, 4 contacts 250V
5 contacts 60V
8 contacts 30V
RATED CURRENT: 3, 4, 5 contacts 4A
8 contacts 2A
PROTECTION CLASS: IP 67
TEMPERATURE: -25°C / +85°C



CONTACTS POSITION FRONT VIEW:

3 CONTACTS		4 CONTACTS		5 CONTACTS		8 CONTACTS	
PIN	WIRE	PIN	WIRE	PIN	WIRE	PIN	WIRE
1	BROWN	1	BROWN	1	BROWN	1	WHITE
2	---	2	WHITE	2	WHITE	2	BROWN
3	BLUE	3	BLUE	3	BLUE	3	GREEN
4	BLACK	4	BLACK	4	BLACK	4	YELLOW
5	---	5	---	5	GREY OR GREEN/YELLOW	5	GREY
						6	PINK
						7	BLUE
						8	RED
CODING REQUIRED TO IEC 61076-2-101							

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2

7	SEE MATRIX	D CARRIER	PVC	TRANSPARENT
6	1	LABEL YELLOW	VINYL	---
5	-	CABLE	SEE SHEET 2	---
4	-	OVERMOLDING BLACK	TPU	---
3	1	COUPLING NUT MALE	BRASS	NICKEL
2	1	INSERT MALE BLACK	PUR	---
1	3 / 4 / 5 / 8	CONTACT M12 MALE	BRASS	SELECTIVE Au OVER Ni
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															
FUNCTIONAL SYMBOLS FA = 0 FE = 0 FV = 0	DIMENSION UNITS		SCALE		CURRENT REV DESC:			molex							
	mm		2:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 703046 DRWN: APAWLAK01 2022/04/12 CHK'D: RSILLER 2022/04/14 APPR: RSILLER 2022/04/14			CSE M12 XP AC MA STR XM SE UNSH							
	ANGULAR TOL ± 1.0 °														
4 PLACES		±		PRODUCT CUSTOMER DRAWING											
3 PLACES		±													
2 PLACES		± 0.05													
DIVISIONAL SYMBOLS	1 PLACE		± 0.3		INITIAL REVISION: DRWN: JMARSZALEK 2016/01/12 APPR: RSILLER 2016/04/08			DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION			
	0 PLACES		± 0.5					1200659185		PSD	000	A10			
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER		CUSTOMER	SHEET NUMBER
								A3-SIZE		120065	SEE TABLE		GENERAL MARKET		1 OF 4

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Others on request).

OPTIONS

8	0	X	0	0	6	X	X	X	X	X	X	X	X
---	---	---	---	---	---	---	---	---	---	---	---	---	---

80=M12x1
Single ended

Contacts:
3=3 Contacts
4=4 Contacts
5=5 Contacts
8=8 Contacts

Heads style:
006=Plug Male Straight

Cable type: See Table

Units:
M=Meter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 units

Overmold color:
Blank (Standard)=Black
A=Grey / G=Black / Y=Yellow
For Cable A09=Yellow

Coupling Nut:
Blank (Standard) & 3=Knurled Brass Ni Plated
1 or 8=Hexagonal Stainless steel
5=Knurled Derlin
7=Knurled Brass Ni Plated, Teflon Coated
Blank=7 for cables I20, I26, K03, K05, P82, S26
9=Knurled / Hexagonal Brass Ni Plated


H= 2 pcs. of I/D Carrier PVC Transparent

CABLE INFORMATION (for more information see Cable Data Sheet).


CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN	SHIELD
E02	3 / 4 / 5 / 8	0.25mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
E03	3 / 4 / 5	0.34mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
H08	3 / 4 / 5 / 8	0.25mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
H09	3 / 4 / 5	0.34mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
P02	3 / 4 / 5 / 8	0.25mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-
P03	3 / 4 / 5	0.34mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-
A09	3	0.34mm²	PVC YELLOW	-	-	-	-	-	-
K03	5	0.82mm²	TPE YELLOW	-	-	-	-	-	-
K05	4	0.38mm²	TPE YELLOW	-	-	-	-	-	-

CABLE LENGTH TOLERANCES

OVER	UP TO AND INCLUDING	TOLERANCES
0	305mm	+19mm
305mm	915mm	+45mm
915mm	1830mm	+56mm
1830mm	3660mm	+89mm
3660mm	7320mm	+165mm
7320mm	14640mm	+317mm
14640mm	30500mm	+610mm
30500mm	>	+2% of finished length



SCALE 1:1

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		molex										
DIVISIONAL SYMBOLS	mm		1:1								CSE M12 XP AC MA STR XM SE UNSH				
	GENERAL TOLERANCES (UNLESS SPECIFIED)														
	ANGULAR TOL ± 1.0°														
	4 PLACES		±		EC NO: 703046 DRWN: APAWLAK01 2022/04/12 CHK'D: RSILLER 2022/04/14 APPR: RSILLER 2022/04/14										
	3 PLACES		±												
	2 PLACES		± 0.05												
1 PLACE		± 0.3		INITIAL REVISION: DRWN: JMARSZALEK 2016/01/12 APPR: RSILLER 2016/04/08											
0 PLACES		± 0.5													
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		120065		SEE TABLE		GENERAL MARKET		2 OF 4	

DOCUMENT STATUS	P1	RELEASE DATE	2022/04/14	06:15:31
-----------------	----	--------------	------------	----------

10		9		8		7		6		5		4		3		2		1	
PART LIST																			
F	No.	Part No.	Engineering No.	Cable Length	No.	Part No.	Engineering No.	Cable Length	No.	Part No.	Engineering No.	Cable Length	No.	Part No.	Engineering No.	Cable Length	F		
	1	1200060046	804006E03M120	12m	36	1200062596	805006E03M003	0.3m	71	1200652157	805006P03M040	4m	106	1200658612	803006P03M040	4m			
	2	1200060047	804006P03M050	5m	37	1200062631	805006P03M120	12m	72	1200652158	805006P03M100	10m	107	1200658613	803006P03M100	10m			
	3	1200060240	803006E03M020	2m	38	1200062799	805006E03M010	1m	73	1200655011	805006P03M005	0.5m	108	1200658653	803006H09M010	1m			
	4	1200060241	803006E03M050	5m	39	1200062830	804006E03M0205	2m	74	1200655051	805006E03M006	0.6m	109	1200658654	803006H09M015	1.5m			
	5	1200060242	803006E03M100	10m	40	1200062877	804006E03M0505	5m	75	1200658016	808006P02M060	6m	110	1200658655	803006H09M020	2m			
	6	1200060256	803006P03M002	0.2m	41	1200062920	804006E03M1005	10m	76	1200658055	803006P03M003	0.3m	111	1200658656	803006H09M030	3m			
	7	1200060257	803006P03M020	2m	42	1200063018	803006P03M0303	3m	77	1200658057	803006P03M035	3.5m	112	1200658657	803006H09M040	4m			
	8	1200060260	803006P03M030	3m	43	1200063077	804006E02M005	0.5m	78	1200658076	804006P03M0505	5m	113	1200658658	808006H08M010	1m			
	9	1200060261	803006P03M050	5m	44	1200063470	804006E03M010H	1m	79	1200658092	805006P03M010	1m	114	1200658659	808006H08M015	1.5m			
E	10	1200060558	804006E03M006	0.6m	45	1200063472	804006P03M200	20m	80	1200658109	808006P02M003	0.3m	115	1200658660	808006H08M020	2m	E		
	11	1200060559	804006E03M010	1m	46	1200063731	805006P03M0065	0.6m	81	1200658110	808006P02M150	15m	116	1200658661	808006H08M030	3m			
	12	1200060560	804006E03M020	2m	47	1200063732	804006E03M0501	5m	82	1200658181	808006P02M010	1m	117	1200658662	808006H08M040	4m			
	13	1200060561	804006E03M030	3m	48	1200063733	804006E03M1001	✱	83	1200658209	805006E03M0061	✱	118	1200658663	808006H08M050	5m			
	14	1200060562	804006E03M050	5m	49	1200063856	804006E03M1501	✱	84	1200658217	805006P03M090	9m	119	1200658727	804006H09M010	1m			
	15	1200060563	804006E03M100	10m	50	1200063941	804006P03M0401	4m	85	1200658223	808006E02M003	0.3m	120	1200658728	804006H09M015	1.5m			
	16	1200060570	804006P03M020	2m	51	1200063953	805006E03M035	3.5m	86	1200658226	808006E02M0038	0.3m	121	1200658729	804006H09M020	2m			
	17	1200060571	804006P03M030	3m	52														

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01

PART LIST

No.	Part No.	Engineering No.	Cable Length
141	1200658890	804006H09M003	0.3m
142	1200658892	803006H09M003	0.3m
143	1200658893	804006E03M050H	5m
144	1200658895	804006H09M200	20m
145	1200658897	805006E03M200	20m
146	1200658913	805006P03M030	3m
147	1200658918	808006E02M005H	0.5m
148	1200658919	808006E02M010H	1m
149	1200659034	804006E02M050	5m
150	1200659036	804006E02M070	7m
151	1200659037	804006E02M100	10m
152	1200659041	808006E02M005	0.5m
153	1200659080	804006E03M020Y	2m
154	1200659104	803006E03M010Y	1m
155	1200659109	804006E02M020	2m
156	1200659110	808006E02M0501	✱ 5m
157	1200659111	803006E02M050	5m
158	1200659141	805006H09M200	20m
159	1200659142	805006H09M300	30m
160	1200659145	805006E03M300	30m
161	1200659149	805006H09M005	0.5m
162	1200659154	804006P03M100Y	10m
163	1200659178	804006P03M075	7.5m
164	1200659179	804006P03M015	1.5m
165	1200659185	805006E03M080	8m
166	1200659186	804006E03M060	6m
167	1200659190	804006P03M250	25m
168	1200659191	804006P03M300	30m
169	1200659192	804006P03M350	35m
170	1200659193	804006P03M400	40m
171	1200659194	804006E03M250	25m
172	1200659195	804006E03M300	30m
173	1200659196	804006E03M350	35m
174	1200659197	804006E03M400	40m
175	1200659198	804006E03M450	45m

No.	Part No.	Engineering No.	Cable Length
176	1200659224	805006P03M200	20m
177	1200659225	805006P03M300	30m
178	1200659254	804006E03M500	50m
179	1200659281	805006P03M150	15m
180	1200659284	808006E02M150	15m
181	1200659285	805006E03M150	15m
182	1200659316	805006P03M005H	0.5m
183	1200659317	805006P03M007H	0.7m
184	1200659318	805006P03M010H	1m
185	1200659319	805006P03M020H	2m
186	1200659320	805006P03M050H	5m
187	1200659321	805006P03M100H	10m
188	1200659322	805006P03M150H	15m
189	1200659323	805006P03M200H	20m
190	1200659324	805006P03M300H	30m
191	1200659325	805006P03M350H	35m
192	1200659367	805006E03M015	1.5m
193	1200659454	805006E03M045	4.5m
194	1200659455	805006E03M075	7.5m
195	1200659513	805006E03M030H	3m
196	1200659514	805006E03M045H	4.5m
197	1200659515	805006E03M075H	7.5m
198	1200659550	804006E03M120H	12m
199	1200659551	805006E03M010H	1m
200	1200659557	804006P03M003	0.3m
201	1200659612	804006P03M080	8m
202	1200659692	803006E02M020	2m
203	1200659983	804006E02M075	7.5m
204	1200659991	804006E02M0705	7m
205	1200656021	804006H09M050H	5m
206	1200659539	808006E02M100	✱✱ 10m
207	1200656293	803006E03M080	8m
208	1200656294	803006E03M120	12m
209	1200656295	804006E03M080	8m
210	1200656297	808006H08M005	0.5m

No.	Part No.	Engineering No.	Cable Length
211	1200650843	803006A09M0208	✱ 2m
212	1200651374	805006K03M020	2m
213	1200652151	805006K03M050	5m
214	1200651129	804006K05M020	2m
215	1200651131	804006K05M050	5m
216	1200651133	804006K05M100	10m
217	1200657191	805006E03M005	0.5m
218	1200656974	805006H09M003	0.3m
219	1200657157	804006P03M002	0.2m
220	1200657158	804006P03M005	0.5m
221	1200657159	804006E03M015	1.5m
222	1200657263	805006H09M250	25m
223			
224			
225			
226			
227			
228			
229			
230			
231			
232			
233			
234			
235			
236			
237			
238			
239			
240			
241			
242			
243			
244			
245			

No.	Part No.	Engineering No.	Cable Length
246			
247			
248			
249			
250			
251			
252			
253			
254			
255			
256			
257			
258			
259			
260			
261			
262			
263			
264			
265			
266			
267			
268			
269			
270			
271			
272			
273			
274			
275			
276			
277			
278			
279			
280			

NOTES:
✱ - Part No. with Yellow PVC overmolding
✱✱ - Part No. with Black PVC overmolding

FUNCTIONAL SYMBOLS

FA

=

0

FE

=

0

FE

=

0

DIVISIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS

mm

SCALE

1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL

±

1.0 °

4 PLACES

±

3 PLACES

±

2 PLACES

±

0.05

1 PLACE

±

0.3

0 PLACES

±

0.5

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

DRAWING

A3-SIZE

SERIES

120065

DOCUMENT NUMBER

1200659185

DOC TYPE

PSD

DOC PART

000

REVISION

A10

SHEET NUMBER

4 OF 4

CURRENT REV DESC:

EC NO: 703046

DRWN: APAWLAK01

CHK'D: RSILLER

APPR: RSILLER

2022/04/12

2022/04/14

2022/04/14

INITIAL REVISION:

DRWN: JMARSZALEK

APPR: RSILLER

2016/01/12

2016/04/08

2022/04/12

2022/04/14

1200659185

PSD

000

A10

DOCUMENT STATUS


P1

RELEASE DATE

2022/04/14

06:15:31

8 POLE MM

FEMALE INSERT 3P
VIEW FROM FRONT SIDE



Pin	WIRE COLOR	Wire color
1	WHITE	WH
2	BROWN	BN
3	GREEN	GN
4	YELLOW	YE
5	GREY	GY
6	PINK	PK
7	BLUE	BU
8	RED	RD

Tablica tolerancji dlugosci Table of length tolerances		
Powyzej Over	Do-wlacznie Up to and including	Tolerancja (+) Tolerance
0	305	+19
305	915	+45
915	1830	+56
1830	3660	+89
3660	7320	+165
7320	14640	+317
14640	30500	+610
30500	>	+2% dlugosci of length

PART No MATRIX

8 0 8 0 0 6 X X X M X X X X X

8-Micro Change
0-Portable
3-3 Core
4-4 Core
5-5 Core
006+ Male straight
H08 - UL Listed LS01 Black
PUR 0.25mm² (24AWG)
P02 - 24AWG BLACK PUR CABLE
E02 - CABLE PVC BLACK 0.25mm²
M-Metres
F-Feet
LENGTH
020-2 METRES
050-5 METRES
200-20 METRES
X OVERMOULD COLOR
Blank=BLACK (Standard)
A=GREY
Y=YELLOW
Coupling Nut Material
Blank-Standard
S-Stainless Steel
5-Bain

VIEW FROM
FRONT SIDE

DRAWING UPDATE EC NO: IPG2013-0156 DRWN:HWALCZAK 2012/07/03 CHKD: APPR:MIWASIECZKO 2012/10/11	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	◎ ▢ FIRST ANGLE PROJECTION	
				mm	INCH	DRAWN BY HWALCZAK	DATE 2012/02/10	TITLE CSE M12 8P AC MA STR PUR XM SE UNSH		
			4 PLACES	± ---	± ---	CHECKED BY JMARSZALEK	DATE 2012/02/16			
			3 PLACES	± ---	± ---	APPROVED BY MDYSZEWSKA	DATE 2012/02/16	MOLEX MOLEX INCORPORATED DOCUMENT NO. SD-120065-001 SHEET NO. 1 OF 1		
			2 PLACES	± ---	± ---	MATERIAL NO. MATRIX DRAWING				
			1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				
ANGULAR ± ---°		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						