








Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
Tape on Reel Packaging according to DIN IEC 60286-3
Verpackungseinheit: 380 Stück
Packaging unit: 380 pcs



Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm


Abspulrichtung - Reel off Direction



374320		rot red	5,4	6,6	0,6	11,4	
374319		grün green	3,6	8,4	5,4	6,6	
374318		blau blue	1,8	10,2	3,6	8,4	
374317		schwarz black	0,6	11,4	1,8	10,2	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

Proprietary notice pursuant to ISO 14014 to be observed.

Information:				Tolerances		 All Dimensions in mm	Scale	3:1		
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.			Designation			
							M 2.54 DRC-B, 20-polig			
b		20.10.2015		www.ERNI.com			324051		I	
Index		Date					Class		DRCB	A3