

Aug. 1. 2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| COUNT   | DESCRIPTION OF REVISIONS   | BY                     | CHKD        | DATE | COUNT   | DESCRIPTION OF REVISIONS | BY            | CHKD             | DATE     |   |
|---|--|------------------------|-------------|------|---|--------------------------|---------------|------------------|----------|---|
| △   |  |                        |             | ..   | △   |                          |               |                  | ..       |   |
| △   |  |                        |             | ..   | △   |                          |               |                  | ..       |   |
| <b>APPLICABLE STANDARD</b>  |  |                        |             |      |   |                          |               |                  |          |   |
| RATING  | OPERATING TEMPERATURE RANGE  | -30°C TO +85°C (NOTE1) |             |      | STORAGE TEMPERATURE RANGE   | -10 °C TO +60 °C         |               |                  |          |   |
|   | VOLTAGE  | 250 V DC               |             |      | APPLICABLE CONTACT  | —                        |               |                  |          |   |
|   | CURRENT  | 3 A                    |             |      | APPLICABLE CONNECTOR  | —                        |               |                  |          |   |
|   |  |                        |             |      | APPLICABLE CABLE  | UL1061 24 AWG TO 28AWG   |               |                  |          |   |
| <b>SPECIFICATIONS</b>   |  |                        |             |      |   |                          |               |                  |          |   |
| ITEM  | TEST METHOD  | REQUIREMENTS           |             |      |   |                          | Q             | T                | A        | T |
| <b>CONSTRUCTION</b>   |  |                        |             |      |   |                          |               |                  |          |   |
| GENERAL EXAMINATION   | VISUALLY AND BY MEASURING INSTRUMENT.  |                        |             |      | ACCORDING TO DRAWING.   |                          |               |                  | ○        | ○ |
| MARKING   | CONFIRMED VISUALLY.  |                        |             |      |   |                          |               |                  | ○        | ○ |
| <b>ELECTRICAL CHARACTERISTICS</b>                                 |  |                        |             |      |   |                          |               |                  |          |   |
| CONTACT RESISTANCE  | 100 mA (DC OR 1000 Hz).  |                        |             |      | 30 mΩ MAX.  |                          |               |                  | ○        | — |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.                        | 20 mV MAX. mA (DC OR 1000 Hz).   |                        |             |      | mΩ MAX.   |                          |               |                  | —        | — |
| INSULATION RESISTANCE   | 500 V DC   |                        |             |      | 1000 MΩ MIN.  |                          |               |                  | ○        | — |
| VOLTAGE PROOF   | 650 V AC FOR 1 min   |                        |             |      | NO FLASHOVER OR BREAKDOWN.  |                          |               |                  | ○        | — |
| <b>MECHANICAL CHARACTERISTICS</b>                                 |  |                        |             |      |   |                          |               |                  |          |   |
| CONTACT INSERTION AND EXTRACTION FORCES                           | BY STEEL GAUGE.  |                        |             |      | INSERTION FORCE   |                          | N MAX.        |                  | —        | — |
|   |  |                        |             |      | EXTRACTION FORCE  |                          | N MIN.        |                  | —        | — |
| INSERTION AND WITHDRAWAL FORCES                                   | MEASURED BY APPLICABLE CONNECTOR.  |                        |             |      | INSERTION FORCE   |                          | N MAX.        |                  | —        | — |
|   |  |                        |             |      | EXTRACTION FORCE  |                          | N MIN.        |                  | —        | — |
| MECHANICAL OPERATION  | TIMES INSERTIONS AND EXTRACTIONS   |                        |             |      | ① CONTACT RESISTANCE:   |                          | mΩ MAX.       |                  | —        | — |
|   |  |                        |             |      | ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  |                          |               |                  | —        | — |
| VIBRATION   | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm. — m/s <sup>2</sup> AT 2 h FOR 3 DIRECTIONS. |                        |             |      | ① NO ELECTRICAL DISCONTINUITY OF #s.  |                          |               |                  | ○        | — |
|   |  |                        |             |      | ② CONTACT RESISTANCE: — mΩ MAX.   |                          |               |                  | —        | — |
|   |  |                        |             |      | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  |                          |               |                  | —        | — |
| SHOCK   | AT m/s <sup>2</sup> DURATION OF PULSE TIMES FOR DIRECTIONS. ms                               |                        |             |      | ① NO ELECTRICAL DISCONTINUITY OF #s.  |                          |               |                  | —        | — |
|   |  |                        |             |      | ② CONTACT RESISTANCE: mΩ MAX.   |                          |               |                  | —        | — |
|   |  |                        |             |      | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  |                          |               |                  | —        | — |
| <b>ENVIRONMENTAL CHARACTERISTICS</b>                              |  |                        |             |      |   |                          |               |                  |          |   |
| DAMP HEAT (STEADY STATE)  | EXPOSED AT 40±2 °C, 90~95% 96 h.   |                        |             |      | ① CONTACT RESISTANCE: 30 mΩ MAX.  |                          |               |                  | ○        | — |
|   |  |                        |             |      | ② INSULATION RESISTANCE: 1000 MΩ MIN.   |                          |               |                  | —        | — |
|   |  |                        |             |      | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  |                          |               |                  | —        | — |
| RAPID CHANGE OF TEMPERATURE                                       | TEMPERATURE -55 → 5 → 35 → 85 → 5 → 35 °C TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.           |                        |             |      | ① CONTACT RESISTANCE: 30 mΩ MAX.  |                          |               |                  | ○        | — |
|   |  |                        |             |      | ② INSULATION RESISTANCE: 1000 MΩ.   |                          |               |                  | —        | — |
|   |  |                        |             |      | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  |                          |               |                  | —        | — |
| RESISTANCE TO SOLDERING HEAT                                      | SOLDER TEMPERATURE, IMMERSION, DURATION. °C FOR s.   |                        |             |      | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.                             |                          |               |                  | —        | — |
| SOLDERABILITY   | SOLDERED AT SOLDER TEMPERATURE, FOR IMMERSION DURATION. °C s.                                |                        |             |      | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMersed. |                          |               |                  | —        | — |
| <b>REMARKS</b>  |  |                        |             |      |   |                          |               |                  |          |   |
| NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.                  |  |                        |             |      | DRAWN   | DESIGNED                 | CHECKED       | APPROVED         | RELEASED |   |
| Unless otherwise specified, refer to MIL-STD-1344.                |  |                        |             |      | <i>T. Niizyaki</i>  | <i>T. Niizyaki</i>       | <i>J. Omi</i> | <i>M. Yamano</i> | <i>E</i> |   |
|   |  |                        |             |      | 95.4.17   | 95.4.17                  | 95.4.18       | 95.4.18          |          |   |
| Note QT: Qualification Test AT: Assurance Test ○: Applicable Test |  |                        |             |      |   |                          |               |                  |          |   |
| <b>HRS</b> HIROSE ELECTRIC CO., LTD.                              |  |                        |             |      | SPECIFICATION SHEET   |                          |               | PART NO.         |          |   |
|   |  |                        |             |      | DF4- <del>X</del> DP-2C   |                          |               |                  |          |   |
| CODE NO. (OLD)  |  |                        | DRAWING NO. |      |   | CODE NO.                 |               |                  | 1        |   |
| CL  |  |                        | ELC4-160366 |      |   | 0078-3                   |               |                  | 1        |   |
|   |  |                        |             |      |   | CL544-0092-4             |               |                  | 1        |   |

TO

