IXYS

X3-Class HiPerFET™ Power MOSFET

IXFN400N15X3

V_{DSS} = 150V
I_{D25} = 400A
$R_{DS(on)}$ ≤ 2.5mΩ

N-Channel Enhancement Mode
Avalanche Rated



miniBLOC, SOT-227
E153432



G = Gate D = Drain
S = Source

Symbol	Test Conditions	Maximum Ratings	
V_{DSS}	T_J = 25°C to 150°C	150	V
V_{DGR}	T_J = 25°C to 150°C, R_{GS} = 1MΩ	150	V
V_{GSS}	Continuous	± 20	V
V_{GSM}	Transient	± 30	V
I_{D25}	T_C = 25°C (Chip Capability)	400	A
$I_{L(RMS)}$	External Lead Current Limit	200	A
I_{DM}	T_C = 25°C, Pulse Width Limited by T_{JM}	900	A
I_A	T_C = 25°C	200	A
E_{AS}	T_C = 25°C	3.5	J
P_D	T_C = 25°C	695	W
dv/dt	$I_S \le I_{DM}$, $V_{DD} \le V_{DSS}$, $T_J \le$ 150°C	50	V/ns
T_J		-55 ... +150	°C
T_{JM}		150	°C
T_{stg}		-55 ... +150	°C
V_{ISOL}	50/60 Hz, RMS t = 1 minute	2500	V~
	$I_{ISOL} \le$ 1mA t = 1 second	3000	V~
M_d	Mounting Torque	1.5/13	Nm/lb.in
	Terminal Connection Torque	1.3/11.5	Nm/lb.in
Weight		30	g

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{DSS}	V_{GS} = 0V, I_D = 3mA	150			V
$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 8mA	2.5		4.5	V
I_{GSS}	V_{GS} = ± 20V, V_{DS} = 0V			± 200	nA
I_{DSS}	V_{DS} = V_{DSS}, V_{GS} = 0V			25	μA
	T_J = 125°C			1.5	mA
$R_{DS(on)}$	V_{GS} = 10V, I_D = 200A, Note 1			2.5	mΩ

Features

- International Standard Package
- miniBLOC, with Aluminium Nitride Isolation
- Isolation Voltage 2500V~
- High Current Handling Capability
- Avalanche Rated
- Low $R_{DS(on)}$

Advantages

- High Power Density
- Easy to Mount
- Space Savings

Applications

- Switch-Mode and Resonant-Mode Power Supplies
- DC-DC Converters
- PFC Circuits
- AC and DC Motor Drives
- Robotics and Servo Controls

© 2019 IXYS CORPORATION, All Rights Reserved.

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max	
g_{fs}	V_{DS} = 10V, I_D = 60A, Note 1	85	145		S
R_{Gi}	Gate Input Resistance		2.15		Ω
C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		23.7		nF
C_{oss}			3730		pF
C_{rss}			140		pF
	Effective Output Capacitance				
$C_{o(er)}$	Energy related, V_{GS} = 0V, V_{DS} = 0.8 • V_{DSS}		2200		pF
$C_{o(tr)}$	Time related, V_{GS} = 0V, V_{DS} = 0.8 • V_{DSS}		5330		pF
$t_{d(on)}$	**Resistive Switching Times**		36		ns
t_r	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 200A		30		ns
$t_{d(off)}$	R_G = 1Ω (External)		210		ns
t_f			19		ns
$Q_{g(on)}$	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 200A		365		nC
Q_{gs}			103		nC
Q_{gd}			87		nC
R_{thJC}				0.18	°C/W
R_{thCS}			0.05		°C/W

Source-Drain Diode

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max	
I_S	V_{GS} = 0V			400	A
I_{SM}	Repetitive, Pulse Width Limited by T_{JM}			1600	A
V_{SD}	I_F = 100A, V_{GS} = 0V, Note 1			1.4	V
t_{rr}	I_F = 150A, -di/dt = 100A/μs, V_R = 100V		132		ns
Q_{RM}			580		nC
I_{RM}			8.8		A

Note 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ T_J = 25°C



Fig. 2. Extended Output Characteristics @ T_J = 25°C



Fig. 3. Output Characteristics @ T_J = 125°C



Fig. 4. $R_{DS(on)}$ Normalized to I_D = 200A Value vs. Junction Temperature



Fig. 5. $R_{DS(on)}$ Normalized to I_D = 200A Value vs. Drain Current



Fig. 6. Normalized Breakdown & Threshold Voltages vs. Junction Temperature



© 2019 IXYS CORPORATION, All Rights Reserved.

Fig. 7. Maximum Drain Current vs. Case Temperature



Fig. 8. Input Admittance



Fig. 9. Transconductance



Fig. 10. Forward Voltage Drop of Intrinsic Diode



Fig. 11. Gate Charge



Fig. 12. Capacitance



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 13. Output Capacitance Stored Energy



Fig. 14. Forward-Bias Safe Operating Area



Fig. 15. Maximum Transient Thermal Impedance



© 2019 IXYS CORPORATION, All Rights Reserved.

SOT-227 Outline



SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.224	1.260	31.10	32.00
B	.303	.327	7.70	8.30
C	.161	.173	4.10	4.40
D	.161	.173	4.10	4.40
E	.161	.173	4.10	4.40
F	.587	.598	14.90	15.20
G	1.181	1.201	30.00	30.50
H	1.488	1.508	37.80	38.30
J	.461	.484	11.70	12.30
L	.030	.033	0.75	0.85
M	.492	.512	12.50	13.00
N	.984	1.004	25.00	25.50
O	.075	.087	1.90	2.20
S	.181	.193	4.60	4.90
U	.000	.005	0.00	0.13

1. NUT MATERIAL:
   STANDARD – Low carbon steel with Ni plating.
   OPTIONAL: – Brass Nut is available.
   PART NUMBER–BN
2. ALL METAL SURFACE ARE PRE NI PLATED EXCEPT TRIM AREA.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2019 IXYS CORPORATION, All Rights Reserved.