

1

2

3

4

5


TECHNICAL CHARACTERISTICS

MATERIAL
 COLOR: BLACK
 STYLE: UL1007

ENVIRONMENTAL
 OPERATING TEMPERATURE: -20°C UP TO 80°C
 COMPLIANCE: LEAD FREE AND ROHS



WIRE DIMENSION
 AWG: 26

PACKAGING
 10 PCS/BAG



Terminal A	662 004 137 22
Terminal B	662 004 137 22

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = ± 0.2 .XX = ± 0.15		
F							
E							
D							
C				APPROVAL: BBu	UNIT: MM	DESCRIPTION: WR-MPC3 3.00 MM FEMALE PRE-CRIMPED CABLE	SIZE A4
B					SCALE:		
A	24-NOV-15	PDF	AK		SHEET: 1/2	WERI PART NO: 662 462 426 030	
REV	DATE	FILE	BY		DRAW: AK		

1

2

3

4

5

Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
F							
E							
D							
C				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE A4
B					SCALE:		
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	
REV	DATE	FILE	BY		DRAW: QL		

D