

Off-the-Shelf (OTS) Mega-Fit Overmolded Cable Assemblies

molex

Molex delivers off-the-shelf and customized Mega-Fit Overmolded Cable Assemblies in multiple circuit sizes and lengths, combining rugged signal connection with a user-friendly interface

Features and Advantages

Custom assemblies for production also available

Meet design needs after prototyping is complete. Molex's extensive design and manufacturing expertise can meet the unique challenges of the most demanding applications



Mega-Fit Cable Assembly capable of carrying a maximum 18.4A of current
High-current terminals deliver more power per linear and square millimeter than most mid-range power products

User-friendly overmolded interface and strain relief

Provides a ruggedized general market connector that is safe and convenient for consumer use. Reduces mechanical stress on wires and terminals.

Fully polarized housings

Prevent accidental mis-mating

Positive latching on housings

Ensures secure retention. Delivers an audible click to provide feedback that connector is fully mated



Fully isolated terminals

Protected against damage during handling and mating

Mega-Fit 4-Circuit Connector

Applications

Consumer

- Office equipment
- Fan tray assemblies
- Gaming and vending
- Washers and dryers
- Heaters and air conditioners

Networking

- Hubs and servers
- Power supplies and distributions

Data/Computing

- Personal computers
- Workstations
- Servers

Industrial

- Machinery and heavy equipment
- Lighting and automation

Commercial Vehicle

- Unsealed electronic control modules
- Power converters



Office Equipment



Vending Machines



Industrial Automation

Off-the-Shelf (OTS) Mega-Fit Overmolded Cable Assemblies



Specifications - Mega-Fit Overmolded Cable Assemblies

ELECTRICAL

Voltage (max.): 300V AC/DC
Current (max.): 18.4A
Dielectric Withstanding Voltage: 2000V AC
Insulation Resistance (min.): 10 Megohms

MECHANICAL

Retention Force (min.): 30.0N
Mating Force (max. per circuit): 6.0N
Unmating Force (max. per circuit): 5.6N
Wire Pullout Force (min.): 220.0N
Durability (min.): 200 cycles

PHYSICAL

Flammability: UL 94V-0
Housing: PBT, Black
Terminal: Copper Alloy
Plating: Gold
Wire/Cable: UL2464, Black, 80°C, xC*12AWG, 300V
Overmolding resin: PVC, Black
Operating Temperature: -20 to +80°C

Ordering Information

Part No.	Description	Length (m)	Number of Circuits
245136	Mega-Fit Overmolded Cable Assembly	0.5	2, 4, 6, 8 and 10
		1	
		2	

Custom Product	Description
Contact Molex	Customized Mega-Fit Overmolded Cable Assembly

www.molex.com/link/overmolded.html

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.