

FEMALE FACE VIEW

3-POLE

1 BROWN
3 BLUE
4 BLACK

4-POLE

1 BROWN
2 WHITE
3 BLUE
4 BLACK

POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
3	1200880022	503000A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]
3	1200880026	503000A10M050	16.40' +6.50" -0 [5.0M +165.1 -0]
3	1200880027	503000A10M100	32.81' +12.50" -0 [10.0M +317.5 -0]
4	1200880047	504000A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]
4	1200880050	504000A10M050	16.40' +6.50" -0 [5.0M +165.1 -0]
4	1200880052	504000A10M100	32.81' +12.50" -0 [10.0M +317.5 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP65
OPERATING TEMPERATURE	-20°C TO +105°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	OVERMOLD	TPE	YELLOW
4	CABLE- 24 AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET: PVC	YELLOW

DESCRIPTION
EC NO: WEU2010-0300
DRWN: REISSNER 2010/01/25
CHKD: FP
APPR: NSTAUDIG 2010/01/29

QUALITY SYMBOLS
= 0
= 0

DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±---
2 PLACES	±---	±.01
1 PLACE	±0.3	±---
ANGULAR ± --- °		

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM

DRAWN BY	DATE
REISSNER	2010/01/25
CHECKED BY	DATE
FP	2010/01/21
APPROVED BY	DATE
NSTAUDIG	2010/01/28

MATERIAL NO.	SEE TABLE
SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE
2:1

DESIGN UNITS
METRIC

THIRD ANGLE PROJECTION

NC 3/4P FE STR SNAP
24AWG PVC

MOLEX INCORPORATED

DOCUMENT NO.
SD-120088-004

SHEET NO.
1

