

FEMALE FACE VIEW

3-POLE

1 BROWN
3 BLUE
4 BLACK

4-POLE

1 BROWN
2 WHITE
3 BLUE
4 BLACK

POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
3	1200880002	503000B09M020	6.56' +3.50" -0 [2.0M +88.9 -0]
3	1200880030	503000B09M050	16.40' +6.50" -0 [5.0M +165.1 -0]
3	1200880004	503000B09M100	32.81' +12.50" -0 [10.0M +317.5 -0]
4	1200880082	504000B09M050	16.40' +6.50" -0 [5.0M +165.1 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP65
OPERATING TEMPERATURE	-25°C TO +80°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	OVERMOLD	TPE	YELLOW
4	CABLE- 24 AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET: PUR	YELLOW

DESCRIPTION
EC NO: WEU2010-0297
DRWN: REISSNER
CHKD: FP
1

2010/01/22
2010/01/29
2010/01/29

DESCRIPTION
REV

QUALITY SYMBOLS
= 0
= 0

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH
4 PLACES ±--- ±---
3 PLACES ±--- ±---
2 PLACES ±--- ±.01
1 PLACE ±0.3 ±---
ANGULAR ± --- °
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM
DRAWN BY DATE
REISSNER 2010/01/22
CHECKED BY DATE
FP 2010/01/21
APPROVED BY DATE
NSTAUDIG 2010/01/28
MATERIAL NO.
SEE TABLE
SIZE A3

DIMENSION STYLE
IN/MM
SCALE 2:1
DESIGN UNITS METRIC
THIRD ANGLE PROJECTION
NC 3/4P FE STR SNAP
24AWG PUR

MOLEX INCORPORATED
DOCUMENT NO. SD-120088-001
SHEET NO. 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

