

	10	9	8	7	6	5	4	3	2	1																																																																																																																																			
F											F																																																																																																																																		
E	<table><tr><th>PART NUMBER</th><th>ENGINEERING P/N</th><th>CABLE LENGTH</th><th>DESCRIPTION</th><th>POWER PAIR</th><th>DATA PAIR</th><th>JACKET MATERIAL</th><th>JACKET O.D.</th><th>VOLTAGE RATING</th><th>CURRENT RATING</th></tr><tr><td>1300390339</td><td>DNB00A-M500</td><td>50 METERS</td><td>MID CABLE</td><td>16 AWG</td><td>20 AWG</td><td>GRAY PVC</td><td>.33/8.4mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390340</td><td>DNB00A-T100</td><td>100 METERS</td><td>MID CABLE</td><td>16 AWG</td><td>20 AWG</td><td>GRAY PVC</td><td>.33/8.4mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390343</td><td>DNDF00A-M500</td><td>50 METERS</td><td>THIN FLEX</td><td>22 AWG</td><td>24 AWG</td><td>GRAY TPE</td><td>.30/7.6mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390344</td><td>DNDF00A-T100</td><td>100 METERS</td><td>THIN FLEX</td><td>22 AWG</td><td>24 AWG</td><td>GRAY TPE</td><td>.30/7.6mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390347</td><td>DNE00A-M500</td><td>50 METERS</td><td>TRAY RATED TRUNK</td><td>16 AWG</td><td>18 AWG</td><td>GRAY PVC</td><td>.53/13.3mm</td><td>600 Volts</td><td>8 Amps</td></tr><tr><td>1300390348</td><td>DNE00A-T100</td><td>100 METERS</td><td>TRAY RATED TRUNK</td><td>16 AWG</td><td>18 AWG</td><td>GRAY PVC</td><td>.53/13.3mm</td><td>600 Volts</td><td>8 Amps</td></tr><tr><td>1300390349</td><td>DNF00A-M500</td><td>50 METERS</td><td>THICK FLEX</td><td>15 AWG</td><td>18 AWG</td><td>GRAY TPE</td><td>.48/12.1mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390350</td><td>DNF00A-T100</td><td>100 METERS</td><td>THICK FLEX</td><td>15 AWG</td><td>18 AWG</td><td>GRAY TPE</td><td>.48/12.1mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390368</td><td>DN00A-M500</td><td>50 METERS</td><td>THICK</td><td>15 AWG</td><td>18 AWG</td><td>GRAY PVC</td><td>.48/12.1mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390369</td><td>DN00A-T100</td><td>100 METERS</td><td>THICK</td><td>15 AWG</td><td>18 AWG</td><td>GRAY PVC</td><td>.48/12.1mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390380</td><td>DND00A-M500</td><td>50 METERS</td><td>THIN</td><td>22 AWG</td><td>22 AWG</td><td>GRAY PVC</td><td>.29/7.2mm</td><td>300 Volts</td><td>4 Amps</td></tr><tr><td>1300390381</td><td>DND00A-T100</td><td>100 METERS</td><td>THIN</td><td>22 AWG</td><td>22 AWG</td><td>GRAY PVC</td><td>.29/7.2mm</td><td>300 Volts</td><td>4 Amps</td></tr></table>										PART NUMBER	ENGINEERING P/N	CABLE LENGTH	DESCRIPTION	POWER PAIR	DATA PAIR	JACKET MATERIAL	JACKET O.D.	VOLTAGE RATING	CURRENT RATING	1300390339	DNB00A-M500	50 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps	1300390340	DNB00A-T100	100 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps	1300390343	DNDF00A-M500	50 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps	1300390344	DNDF00A-T100	100 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps	1300390347	DNE00A-M500	50 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps	1300390348	DNE00A-T100	100 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps	1300390349	DNF00A-M500	50 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps	1300390350	DNF00A-T100	100 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps	1300390368	DN00A-M500	50 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps	1300390369	DN00A-T100	100 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps	1300390380	DND00A-M500	50 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps	1300390381	DND00A-T100	100 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps	E
PART NUMBER	ENGINEERING P/N	CABLE LENGTH	DESCRIPTION	POWER PAIR	DATA PAIR	JACKET MATERIAL	JACKET O.D.	VOLTAGE RATING	CURRENT RATING																																																																																																																																				
1300390339	DNB00A-M500	50 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps																																																																																																																																				
1300390340	DNB00A-T100	100 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps																																																																																																																																				
1300390343	DNDF00A-M500	50 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps																																																																																																																																				
1300390344	DNDF00A-T100	100 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps																																																																																																																																				
1300390347	DNE00A-M500	50 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps																																																																																																																																				
1300390348	DNE00A-T100	100 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps																																																																																																																																				
1300390349	DNF00A-M500	50 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps																																																																																																																																				
1300390350	DNF00A-T100	100 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps																																																																																																																																				
1300390368	DN00A-M500	50 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps																																																																																																																																				
1300390369	DN00A-T100	100 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps																																																																																																																																				
1300390380	DND00A-M500	50 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps																																																																																																																																				
1300390381	DND00A-T100	100 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps																																																																																																																																				
D											D																																																																																																																																		
C											C																																																																																																																																		
B											B																																																																																																																																		
A	<table><tr><td colspan="10">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr><tr><td colspan="2">DIMENSION UNITS INCH/MM</td><td colspan="2">SCALE NTS</td><td colspan="4" rowspan="2">CURRENT REV DESC: OBSOLETED PART NUMBER AS PER PCN#508517</td><td colspan="2" rowspan="2"> molex </td></tr><tr><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2"></td></tr><tr><td></td><td></td><td>MM</td><td>INCH</td><td colspan="4" rowspan="5">EC NO: 667105 DRWN: SUGEEB 2021/05/27 CHK'D: GGA 2021/06/29 APPR: GGA 2021/06/29 INITIAL REVISION: DRWN: R.STONE 2010/01/19 APPR: JFMURPHY 2010/01/20</td><td colspan="2">DOCUMENT NUMBER</td><td>DOC TYPE</td><td>DOC PART</td><td>REVISION</td></tr><tr><td>4 PLACES ±</td><td></td><td></td><td></td><td colspan="2">SD-130039-026</td><td>PSD</td><td>001</td><td>C</td></tr><tr><td>3 PLACES ±</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td></tr><tr><td>2 PLACES ±</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td></tr><tr><td>1 PLACE ±</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td></tr><tr><td>0 PLACES ±</td><td></td><td></td><td></td><td colspan="2">ANGULAR TOL ± 0.5 °</td><td colspan="2">THIRD ANGLE PROJECTION </td><td>DRAWING B-SIZE</td><td>SERIES 130039</td><td colspan="2">MATERIAL NUMBER SEE TABLE</td><td>CUSTOMER GENERAL MARKET</td><td>SHEET NUMBER 1 OF 1</td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>										THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										DIMENSION UNITS INCH/MM		SCALE NTS		CURRENT REV DESC: OBSOLETED PART NUMBER AS PER PCN#508517				molex		GENERAL TOLERANCES (UNLESS SPECIFIED)						MM	INCH	EC NO: 667105 DRWN: SUGEEB 2021/05/27 CHK'D: GGA 2021/06/29 APPR: GGA 2021/06/29 INITIAL REVISION: DRWN: R.STONE 2010/01/19 APPR: JFMURPHY 2010/01/20				DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION	4 PLACES ±				SD-130039-026		PSD	001	C	3 PLACES ±									2 PLACES ±									1 PLACE ±									0 PLACES ±				ANGULAR TOL ± 0.5 °		THIRD ANGLE PROJECTION 		DRAWING B-SIZE	SERIES 130039	MATERIAL NUMBER SEE TABLE		CUSTOMER GENERAL MARKET	SHEET NUMBER 1 OF 1	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS														A																													
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																													
DIMENSION UNITS INCH/MM		SCALE NTS		CURRENT REV DESC: OBSOLETED PART NUMBER AS PER PCN#508517				molex																																																																																																																																					
GENERAL TOLERANCES (UNLESS SPECIFIED)																																																																																																																																													
		MM	INCH	EC NO: 667105 DRWN: SUGEEB 2021/05/27 CHK'D: GGA 2021/06/29 APPR: GGA 2021/06/29 INITIAL REVISION: DRWN: R.STONE 2010/01/19 APPR: JFMURPHY 2010/01/20				DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION																																																																																																																																	
4 PLACES ±								SD-130039-026		PSD	001	C																																																																																																																																	
3 PLACES ±																																																																																																																																													
2 PLACES ±																																																																																																																																													
1 PLACE ±																																																																																																																																													
0 PLACES ±				ANGULAR TOL ± 0.5 °		THIRD ANGLE PROJECTION 		DRAWING B-SIZE	SERIES 130039	MATERIAL NUMBER SEE TABLE		CUSTOMER GENERAL MARKET	SHEET NUMBER 1 OF 1																																																																																																																																
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS																																																																																																																																													
	DOCUMENT STATUS	P1	RELEASE DATE	2021/06/29 11:13:50	9	8	7	6	5	4	3	2	1																																																																																																																																