


KYCON, Inc. 305 Digital Drive, Morgan Hill, CA 95037 (408)494-0330







Material and Finish

Shell: Steel, nickel plated

Insulator: PBT thermoplastic
with glass-fiber reinforcement,
UL94V-0 rated
Color: Black

Contact Material:
Plug - Brass

Contact Plating Options:

Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact

15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact

30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

Rated Current: 1.5A

Rated Voltage: 30Vac

Insulation Resistance:
more than 1000 megohms at 500V DC

Contact Resistance:
13 milliohms max.

Dielectric Withstanding Voltage:
1000V for 1 minute

Operating Temperature:
-55°C to +105°C

Ordering Information	
Part Number	Contact Area Plating Finish
K86X-EA-15P	Gold Flash (standard)
K86X-EA-15P-15	15u" Gold (15 option)
K86X-EA-15P-30	30u" Gold (30 option)

RoHS COMPLIANT

E140125 LR78160

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY
A1	10/31/05	New Drawing	R. Aguirre	H. MA
A2	1/17/08	ECO# 07-052	WILL H.	H. MA
A3	9/30/14	ECO#14-028	H. MA	P. DalCanto
A4	12/31/17	ECO #17-033	J. Elbanna	C. Furumasu

DRAWN BY	DATE
R. Aguirre	10/31/05
	UNITS
	mm

K86X-EA-15P

High Density Vertical Mount D-Sub

15 pin plug, solder cups,RoHS Compliant

KYCON