

PART NUMBER	ENGINEERING NUMBER
1300680022	1C4130-001

NOTE:

- 1) LABEL IS MARKED WITH P/N, DATE CODE, VOLTAGE & AMPERAGE
- 2) ELECTRICAL DATA:
REDUCING ADAPTER QC TO MC
POLES: 4
MAX. VOLTAGE: 600V AC/DC
MAX.CURRENT: 15A
PROTECTION: IP67
TEMPERATURE RANGE: -20°C TO 90°C
- 3) PACKAGING:
ASSEMBLIES ARE BAGGED SEPERATELY IN POLY BAGS WITH BAR CODE LABEL ATTACHED TO THE OUTSIDE OF THE BAG.
- 4) ASSEMBLY IS RoHS COMPLIANT
- 5) CERTIFICATION:
UL LISTED/CSA CERTIFIED , FILE E258922

8	1	LABEL	PLASTIC FILM	BLACK/YELLOW
7	4	MC SOCKET CONTACT	COPPER ALLOY	GOLD PLATED
6	1	MC INSERT	PVC	BLACK
5	1	MC COUPLING NUT	ZINC ALLOY	BLACK E-COAT
4	4	QC PIN CONTACT	COPPER ALLOY	GOLD PLATED
3	1	QC INSERT	PVC	BLACK
2	1	QC COUPLING NUT	ALUMINUM	BLACK ANODIZE
1	1	OVERMOLD	PVC	GRAY
ITEM	QTY	DESCRIPTION	MATERIAL	FINISH

RELEASED EC NO: WNA2010-0424 DRWN: KJOZWIK 2010/01/12 CHKD: BWOODMAN APPR: JFMURPHY 2010/01/15	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION			
						IN/MM		1:1	INCH				
				mm	INCH	DRAWN BY	DATE	TITLE BRAD POWER PASS-THRU 4 POLE QC DC MALE/MC FEMALE					
			4 PLACES	±---	±---	KJOZWIK	2010/01/12						
			3 PLACES	±---	±.005	CHECKED BY	DATE	MOLEX INCORPORATED					
			2 PLACES	±0.13	±.010	BWOODMAN	2010/01/11						
			1 PLACE	±0.25	±.020	APPROVED BY	DATE	MATERIAL NO. SEE TABLE					
			ANGULAR ±1/2°			JFMURPHY	2010/01/15						
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO. SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
						SIZE B							

