
Für diese Unterlage behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustereintragung. Sie darf ohne unsere vorherige schriftliche Zustimmung weder vervielfältigt noch sonstwie benutzt, noch Dritten zugänglich gemacht werden.

Nur rot gestempelte oder auf Laufkarte gedruckte Dokumente unterliegen dem Änderungsdienst und sind zur Fertigung freigegeben.
Only red stamped or on jobcard printed documents are managed. These documents are approved for production.


All Rights reserved, including possible patents or trademarks. Documents shall not be provided to a third party or duplicated in any form without prior written permission.

CAD: Pro/ENGINEER


Additional coding
View in direction A



GKCWBM-P07UB00-000L
Mechanical coding: B
Color coding: red





GKCWCM-P07UB00-000L
Mechanical coding: C
Color coding: blue




GKCWDM-P07UB00-000L
Mechanical coding: D
Color coding: green


Panel cut-out






GKCWAM-P07UB00-000L
Mechanical coding: A
Color coding: light brown





Delivery condition
3:1

PCB-Layout
View in mating direction A
8:1



Technical information

- Print contacts 3)
- Current load: 1A@Δt40° (Single contact)
- Test voltage: 750V (acc. SAE AS 13441:1998, Contact to contact)
- Rated voltage: 250V (acc. SAE AS 13441:1998) 2)

1) ODU recommend an additional locking of the nut with adhesive (e.g. Loctite 2701) to the screw thread.

2) Maximal operating voltage at sea level up to 2.000 m. Rated voltage applies no other electrical safety standard. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. This must be evaluated in the frame of equipment engineering.

3) For pcb assembling see pcb assembly instruction 009.410.120.000.000

All shown connectors are according to DIN EN 61984:2009 connectors without breaking capacity (COC)!

index	notice	date	name

General tolerances to DIN ISO 2768-mK
Toleration to DIN ISO 8015

	date	name
2014		
prep.	14.11.	Unterblüm.
app.		
norm.		

ODU A perfect alliance.

PE-modell-nr.:

CAD-nr.: 00058453

sheet.:

designation: Receptacle

scale: 6:1

drawing nr.: GKCW.M-P07UB00-000L

copy nr.

replacement for: