

- straight action principle

- ratchet release

- simple pressure adjustment with locking device

- simple contact-positioning


- precisely ground profiles

- ergonomic soft grips, colour: yellow (RAL 1003) / black

- fully recyclable

- application range: high current contacts

| for high current contacts: | | | |
|----------------------------|-------------------|----------------------|-----|
| part no. | operating current | wire gauge | AWG |
| 09 03 000 6113 | 10 A | 1,5 mm ² | 16 |
| 09 03 000 6114 | 20 A | 4,0 mm ² | 12 |
| 09 03 000 6115 | 40 A | 10,0 mm ² | 8 |

| | | | | | | | | |
|-------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------|----------------------|----------------------------------------------------|-----------------------------|--------------------|------------------------|-----------------------------------------------------------|
|  | All rights reserved Department EL PD | All Dimensions in mm Original Size DIN A4 | | Scale 1:1 | Free size tol. | Ref. | | |
| | | HARTING Electronics GmbH D-32339 Espelkamp | Created by STORCK | Inspected by WAERMKER | Standardisation HOFFMANN | Date 2018-12-05 | State Final Release | Doc-Key / ECM-Nr. 100806883/UGD/000/A 5000001414.02 |
| | | | | Title crimpool for high current contacts | | | Rev. A | Page 1/1 |
| | | | | Type TB | Number 09990000196 | | | |