


KYCON, Inc. 305 Digital Drive, Morgan Hill, CA 95037 (408)494-0330




Recommended PCB Layout
(top view)





Boardlock not shown in this view



Material And Finish

Shell: Steel Material, Nickel Plated

Insert: PBT Thermoplastic,
Black Color, 30%
Glass Filled, UL 94V-0 Rated

Contact Material:
Plug - Brass

Contact Plating:
Standard:
Gold flash on mating end,
tin on termination end, with
entire contact nickel underplated

-15 Option:
15u" gold on mating end,
tin on termination end, with
entire contact nickel underplated

-30 Option:
30u" gold on mating end,
tin on termination end, with
entire contact nickel underplated

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Dielectric Withstanding Voltage:
1000V (rms) AC for 1 minute

Insulation Resistance:
more than 1000 Megohm
at 500V DC

Contact Resistance:
13 milliohm max.

Operating Temperature
-55°C to +105°C

Ordering Information	
Part Number	Contact Area Plating Finish
K85X-AD-15P-BRJ	Gold Flash (standard)
K85X-AD-15P-BRJ15	15u" Gold (15 option)
K85X-AD-15P-BRJ30	30u" Gold (30 option)

RoHS COMPLIANT

C US
LR78160

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY
A1	1/05/06	New Drawing	R. Aguirre	H. MA
A2	1/8/08	ECO # 07-052	WILL H.	H. MA
A3	12/31/17	ECO #17-030	J. Elbanna	C. Furumasu

DRAWN BY	DATE
R. Aguirre	10/12/05
	UNITS
	mm

K85X-AD-15P-BRJ

Vertical PCB Mount D-Sub ,RoHS Compliant

15 pos. male w/boardlocks & JS-1055 jackscrews installed

KYCON