
DATASHEET

Photo-link Light Transmitter Unit
PLT237/T10WH



Features

- High speed signal transmission（25Mbps NRZ Signal）
- TTL interface compatible
- +3~+5V single power source
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH
- Compliance Halogen Free(Br<900ppm,Cl<900ppm,Br+Cl<1500ppm)

Description

The opto-electrical component is assembled with a 660nm AlGaInP LED and a driver IC. It transforms the electrical signal to optical signal and be transmitted by 1mm diameter plastic optical fiber.
The component is operated at +3~+5V and has good performance at low dissipation current, steady light output and efficient light coupling.

Applications

- Digital audio equipment
- CD player
- DVD player

Device Selection Guide

Chip		Operating Voltage (Vcc)	Dissipation Current (mA)		Fiber Coupling Light Output (dBm)		
Material	λp(nm)		Typ.	Max.	Min.	Typ.	Max.
AlGaInP	660	+3.0~5.0	5.5	10	-21	---	-14

Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1

Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Unit
Supply Voltage	Vcc	-0.5 to 7	V
DC Input Voltage	Vin	-0.5 to Vcc+0.5	V
Storage Temperature	Tstg	-40 to 85	ºC
Operating Temperature	Topr	-40 to 85	ºC
Soldering Temperature	Tsol	260*	ºC
Human Body Model ESD	HBM	3K	V
Machine Model ESD	MM	300	V

Notes: Soldering time≦10 seconds.

Recommended Operating Conditions

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Supply Voltage	Vcc	-	2.7	3.0	5.0	V

Electro-Optical Characteristics (Ta=25ºC,Vcc=5.0V, 25Mbps)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Peak Emission Wavelength	λp		640	660	680	nm
Transmission Rate		NRZ Signal	DC	-	25	Mbps
Fiber Coupling Output Power	Pf	* Measuring Method 1	-21	-	-14	dBm
Dissipation Current	Icc	* Measuring Method 1	3	-	10	mA
High Level Input Voltage	Vih		2	-	-	V
Low Level Input Voltage	Vil		-	-	0.8	V
Rise Time	Tr	[1] ; *2 NRZ Code VFLED = 2.0V	-	15	20	ns
Fall Time	Tf		-	15	20	ns
Low to High Delay Time	tpLH	* Measuring Method 2	-	-	100	ns
High to Low Delay Time	tpHL	* Measuring Method 2	-	-	100	ns
Pulse Width Distortion	Δtw	* Measuring Method 2	-20	-	20	ns
Jitter	Δtj	* Measuring Method 2	-	1.5	20	ns

*Note 1 : All Plastic Optical Fiber（980/1000um）

Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1


Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)

*Circuit Layout Notice:
When power is off, it must be cut off together in Vin and Vcc pin.
If it only has Vcc power-off, LED will sure to be no output power.


Vcc	Vin	LED Condition
2.7~5.0	High	ON
2.7~5.0	Low	OFF
2.7~5.0	FLOATING	OFF
FLOATING	0~Vcc	OFF

Measuring Method

*1 Measuring method of optical output coupling fiber and dissipation current




*2 Pulse response measuring method



Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1
www.everlight.com
Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)

Package Dimension



Pin Function:


1.Vin
2.Vcc
3.GND
4.NC
5.NC

Notes:


1.All dimensions are in millimeters.

2.General Tolerance :±0.3mm

Using Method



PCB Layout for Electrical Circuit




Notes:
1.unit:mm
2.Dimension Tolerance:±0.25mm
3.Substrate Thickness:1.6mm

Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1

Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)

Label Explanation



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number
- X: Month
- Reference: Identify Label Number
- MADE IN XXXXXX: Place of production

Packing Quantity Specification

1. 60 pcs/tube
2. 36 tube/Inner box
3. 4 Inner box/Outside box

Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1

Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)

Notes

1. Above specification may be changed without notice. Everlight Americas will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. Everlight Americas assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of Everlight Americas Inc. Please don't reproduce or cause anyone to reproduce them without Everlight Americas's consent.
4. Storage

   The should be stored at 30°C or less and 70%RH or less after being shipped from Everlight and the storage life limits are 3 months. If the products are stored for 3 months or more, they can be stored for a year in a sealed container with a nitrogen atmosphere and moisture absorbent material.

   Please avoid rapid transitions in ambient temperature, especially, in high humidity environments where condensation can occur.
5. After opening the package, the devices must be stored at 10°C~30°C and ≤ 60%RH, and used within 24 hours (floor life)

Disclaimer

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.

EVERLIGHT ELECTRONICS CO., LTD.
Office: No 6-8,Zhonghua Rd., Shulin Dist.,
New Taipei City 23860, Taiwan, R.O.C
Tel: 886-2-2685-6688
Fax: 886-2-2685-6897
http://www.everlight.com

Copyright © 2010, Everlight All Rights Reserved. Release Date :2021.03.22 . Issue No: DPL-0000256 _Rev.1

Ver.:1 Release Date:03/29/2021 狀態:Approved(正式發行)