



DB25 AND XLRM WIRING CHART

XLR (CHANNEL)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	BROWN	24	12	25
2	RED	10	23	11
3	ORANGE	21	9	22
4	YELLOW	7	20	8
5	GREEN	18	6	19
6	BLUE	4	17	5
7	PURPLE	15	3	16
8	GRAY	1	14	2

PART NO.	CABLE LENGTH "X"
DB25M02XLRM	2.00 FT +/- 1.50 IN
DB25M03XLRM	3.00 FT +/- 1.50 IN
DB25M10XLRM	10.00 FT +/- 1.50 IN

NOTES:

1. BREAKOUT CABLE LENGTH: 18.00 +/- 0.75 INCHES. SEE TABLE FOR COLOR.

B 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

B 3. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.

B 4. MATERIALS:
 XLR MALE CONNECTOR:
 HANDLE - ZINC ALLOY, NICKEL PLATED
 HOUSING - ZINC ALLOY, NICKEL PLATED
 INSULATOR - THERMOPLASTIC, GREEN
 CONTACT PINS - COPPER ALLOY, SILVER PLATED
 H.S. TUBING - THERMOPLASTIC
 DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS
 JACKSCREWS - STAINLESS STEEL

5. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

REVISIONS					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.02 - THREE PLACE DECIMALS ±0.005	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
REV	ECO NUMBER	DATE	BY	APVD		SIZE	WIDTH	MULT	LBS/M	TEMPER	
C	26795	7-8-11	TO	TJK	DO NOT SCALE DRAWING	FINISH SPEC No.				MATERIAL SPEC No.	
B	26637	10/11/10	RS	TJK		FIRST USED ON					
A	25716	10/03/07	JGK	TJK		DATE DRAWN	BY	CHKD	APVD		SCALE
						9/12/06	JGK	RS	TJK	2:1	
					NAME					PART No.	REV
					DB25M TO 8 XLR MALES, RoHS					DB25M__XLRM	C