



Circular Connectors IP68 Circular Connectors AC 167 micro AC 167 REST/2 M16

panel mount plug, 2 pole, voltage rating: 500 V, current rating: 10.0 A



Order Info

reference number (ref. no.)	72876216
PU	200
EAN	4028012133833

Type

type	panel mount plug
number of poles	2 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	1.0 mm ²
connection type	screw
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	500 V
current rating	10.0 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.25 mm ²
core cross-section max.	1.0 mm ²
impulse voltage rating	2.5 kV
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
IP code	IP68
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0 mm
Assembly Contact Screw	0.5x3.0 / ⚙ 0.2 Nm
wall thickness max.	7.0 mm

housing hole diameter	M16
tightening torque lock nut	1,5 Nm
lower limit temperature	-40 °C
upper limit temperature	125 °C

Accessories

AC 167 RVKS M16	729042
------------------------	--------