




Connectors System AC 164 Plug and Socket Connectors Tall Version

AC 164 ST/ 3 WS

plug, 3 pole, white, coding: 1 (mains), voltage rating: 250 V, current rating: 16.0 A, cross-section rating: 1.5 mm², connection type: screw



Order Info

reference number (ref. no.)	146053
PU	200
EAN	4028012122547

Type

type	plug
number of poles	3 pole
clamping units per pole	1
colour	white
coding	1 (mains)
cross-section rating	1.5 mm ²
connection type	screw
PE function	yes
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	250 V
current rating	16.0 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	1.5 mm ²
impulse voltage rating	4.0 kV
flammability rating	V-2
max. Ambient Temperature Operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0 mm

Approvals

acc. to EN 61535[Download PDF](#)

acc. to UL[Download PDF](#)

Accessories

AC 164 BC/ 3 SW149563

AC 164 BC/ 3 WS149553
