




Screw Terminal Blocks

230/12

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 2.5 mm², pin spacing: 8.00 mm, mounting hole diameter: 2.8 mm, fixing: screw, voltage rating: 450 V, current rating: 24.0 A



Order Info

reference number (ref. no.)	121212
PU	50
EAN	4028012100002

Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm ²

Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
flammability rating	V-2
min. Umgebungstemperatur	-40 °C
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
mounting hole diameter	2.8 mm
pin spacing	8.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------

acc. to CSA	Download PDF
--------------------	------------------------------

Accessories

230 BZ/12	191212
------------------	--------

ZEL 110	196420
----------------	--------