## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90788

Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability. True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits.

All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.

Elbow features a smooth bore to ease cable installation.

PA66 nylon material has high resistance to salts, oils, weak acids, and solvents.

Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.



HelaGuard NM Ultra IP68 Fitting, 90-Degree Elbow, 0.75" NPT Thread, .75" Dia., PA66, Black, 1/pkg

Article Number 166-90788

**Type** HGU075-90-0750

Color Black (BK)

Quantity Per pack

Product Description	Elbow Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.
Short Description	HelaGuard NM Ultra IP68 Fitting, 90-Degree Elbow, 0.75" NPT Thread, .75" Dia., PA66, Black, 1/pkg
Global Part Name	HGU075-90-0750-PA66-BK
Length L (Imperial)	2.60
Length L (Metric)	66.0
Variant	90° Elbow
Outside Diameter OD (Imperial)	1.73
Outside Diameter OD (Metric)	44.0

0.75

28

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

**Nominal Diameter (Imperial)** 

**Nominal Diameter (Metric)** 

Flammability Self-extinguishing

Halogen Free Yes

Operating Temperature -58°F to +275°F (-50°C to +135°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

**Customs Number** 3926909988

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions