HellermannTyton

Specification Sheet

Part Number: 170-03177



Weave construction adjusts to twisting and flexing without creating wrinkles or bends.

Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.

Color options available to provide easy visual and safety identification of critical wiring components.

Expands to 150% of nominal diameter for fast, easy installation.

Braided Sleeving, Expandable, 0.125" Dia, PET, Black, 225 ft/reel

Article Number	170-03177
Туре	BSP180
Color	Black (BK)
Quantity Per	reel
Product Description	Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation. Commonly used in electrial and industrial wire harnessing application where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.

Short Description	Braided Sleeving, Expandable, 0.125" Dia, PET, Black, 225 ft/reel			
Global Part Name	BSP180-PET-BK			
Length L (Imperial)	225.0			
Length L (Metric)	68.6			
Bundle Diameter Min (Imperial)	0.094			
Bundle Diameter Min (Metric)	2.4			
Bundle Diameter Max (Imperial)	0.25			
Bundle Diameter Max (Metric)	6.4			
Diameter D (Imperial)	0.25			
Diameter D (Metric)	6.4			
Nominal Diameter (Imperial)	0.125			
Nominal Diameter (Metric)	3.18			

Material

Polyester (PET)

Material Shortcut

Flammability	FAR 25 FMVSS 302 UL 94 V-0	
Halogen Free	Yes	
Operating Temperature	-94°F to +257°F (-70°C to +125°C)	
Reach Compliant (Article 33)	Yes	
ROHS Compliant	Yes	
UL Recognized (US)	Yes	
Package Quantity (Imperial)	225	
Package Quantity (Metric)	68.58	
Customs Number	5808100000	

© 2022 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions