PCA.0A.250.NTLC29Z

SUMMARY

Wires

Coax	1

Image is for illustrative purpose only

Series	0A
Termination type	Female solder
IP rating	50
AWG wire size	0.00 - 0.00
Cable Ø	2.50 - 2.80 mm
Status	active
Matching parts	FFA.0A.250.NTAC29Z

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PCA*: Straight receptacle with cable collet and nut for fitting a bend relief
Keying	
Housing Material	Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces
Variant	Z : Nut for fitting a bend relief
Weight	8.73 g

Performance

Configuration	0A.250 : 1 Coax (50 Ohm)
Insulator	
Rated Current	

Specifications


Contact Type: Coaxial 50 Ohm (Solder)

Others

Endurance (Shell): 5000 mating cycles
Salt Spray Corrosion: >144 hr

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS





Dimensions

	A	B	L	S1	S2	S3
mm.	9	11	36.5	8	9	9
in.	0,35	0,43	1,44	0,31	0,35	0,35

RECOMMENDED BY LEMO

Tools

Cables

17420	PVC	Black	
17450	COPOLYMER	Black	
18700	PTFE	White	
18800	PTFE	White	
31600	PTFE	Brown	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.50.RG3.16U28M	PTFE	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.