

## Part Number : <u>936010129</u>

Series Number : 93601 Product Category : Heavy-Duty Connectors Product Description : GWconnect Screw Terminal Insert, Female, 4-Pole, 10A, without Wire Protection, Silver (Ag) Plated Contacts, Size 3A «21x21» Status : Active Engineering Number : 7204.6002.0

## Product Environment Compliance

#### Compliance

| GADSL/IMDS         | Not Relevant   |
|--------------------|--|
| China RoHS         | <b>@</b>   |
| EU ELV             | Not Relevant   |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                               |
| REACH SVHC         | Contains Lead per D(2023)8585-DC<br>(23 Jan 2024)            |
| EU RoHS            | Compliant with Exemption 6(c);<br>6(c); 6(c) per EU 2015/863 |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

## **Part Details**

#### General

| Status   | Active                |
|----------|-----------------------|
| Category | Heavy-Duty Connectors |
| Series   | 93601                 |

| Description    | GWconnect Screw Terminal Insert,<br>Female, 4-Pole, 10A, without Wire<br>Protection, Silver (Ag) Plated<br>Contacts, Size 3A «21x21» |
|----------------|--|
| Component Type | Inserts - Screw Terminal   |
| Insert Series  | S-A3/4   |
| Product Family | GWconnect Heavy Duty Connectors<br>(HDC)   |
| Product Name   | GWconnect  |
| Standard       | CSA C22.2 NO. 182.3, EN 60664-1,<br>EN 61984, UL 1977  |
| UPC            | 887191871974   |

# Agency

| CSA | 256883  |
|-----|---------|
| UL  | E249674 |

## Electrical

| Current - Maximum per Contact | 10.0A       |
|-------------------------------|-------------|
| Voltage - Maximum             | 230V / 400V |
| Wire Protection               | No          |

# Physical

| Component Size                 | 3A «21x21»     |
|--------------------------------|----------------|
| Durability (mating cycles max) | 500            |
| Gender                         | Female         |
| Insert Color                   | Grey           |
| Material - Contact             | Copper Alloy   |
| Material - Insert              | Polycarbonate  |
| Material - Plating             | Silver         |
| Net Weight                     | 13.100/g       |
| Number of Rows                 | 2              |
| Packaging Type                 | Bag            |
| Polarized to Mating Part       | Yes            |
| Poles                          | 4              |
| Stripping Length               | 6.00mm         |
| Temperature Range - Operating  | -40° to +125°C |

| Tightening Test Torque    | 0.25 Nm   |
|---------------------------|-----------|
| Wire Size (AWG)           | 14-20     |
| Wire Size mm <sup>2</sup> | 0.50-2.50 |

## Mates With / Use With

## Mates with Part(s)

| Description  | Part Number      |
|--|------------------|
| GWconnect Screw Terminal Insert,<br>Male, 4-Pole, 10A, without Wire<br>Protection, Silver (Ag) Plated<br>Contacts, Size 3A «21x21» | <u>936010133</u> |

## Use with Part(s)

| Description | Part Number                           |
|-------------|---------------------------------------|
| Use With    | Size 3A «21x21» Hoods and<br>Housings |

This document was generated on Jun 02, 2024