

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 12-position, PUR/PVC, black RAL 9005, shielded, free cable end, on Socket angled M12 SPEEDCON, coding: A, cable length: 5 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Save time, thanks to installation with SPEEDCON fast locking system
- Save space – with high-pos. connectors
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1430187             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF03                |
| Product key                          | BF1CNA              |
| Catalog page                         | Page 214 (C-2-2019) |
| GTIN                                 | 4046356322454       |
| Weight per piece (including packing) | 487.1 g             |
| Weight per piece (excluding packing) | 467.3 g             |
| Customs tariff number                | 85444290            |
| Country of origin                    | DE                  |

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Standard              |
| Number of positions  | 12                    |
| No. of cable outlets | 1                     |
| Shielded             | yes                   |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | V0                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuZn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | PA 6.6                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 30 V AC                    |
|                       | 30 V DC                    |
| Nominal current $I_N$ | 1.5 A                      |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

#### Connection 2

|                     |                            |
|---------------------|----------------------------|
| Type                | Socket angled M12 SPEEDCON |
| Number of positions | 12                         |

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

|              |          |
|--------------|----------|
| Locking type | SPEEDCON |
| Coding type  | A        |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 5 m |
|--------------|-----|

### Black PUR/PVC twisted pair [35T]

|                                               |                                                                                    |
|-----------------------------------------------|------------------------------------------------------------------------------------|
| Dimensional drawing                           |  |
| Cable weight                                  | 87 kg/km                                                                           |
| UL AWM Style                                  | 20233 / 1061 (80°C/300 V)                                                          |
| Number of positions                           | 12                                                                                 |
| Shielded                                      | yes                                                                                |
| Cable type                                    | Black PUR/PVC twisted pair [35T]                                                   |
| Conductor structure signal line               | 18x 0.10 mm                                                                        |
| AWG signal line                               | 26                                                                                 |
| Conductor cross section                       | 12x 0.14 mm <sup>2</sup> (Signal line)                                             |
| Wire diameter incl. insulation                | 1 mm ±0.05 mm (Signal line)                                                        |
| External cable diameter                       | 8.50 mm ±0.2 mm                                                                    |
| Outer sheath, material                        | PUR                                                                                |
| External sheath, color                        | black RAL 9005                                                                     |
| Conductor material                            | Tin-plated Cu litz wires                                                           |
| Material wire insulation                      | PVC                                                                                |
| Single wire, color                            | white-brown, green-yellow, gray-pink, blue-red, black-violet, gray/pink-red/blue   |
| Twisted pairs                                 | 2 cores to the pair                                                                |
| Overall twist                                 | Six pairs around the filler to the core                                            |
| Optical shield covering                       | 85 %                                                                               |
| Max. conductor resistance                     | ≤ 142 Ω/km (at 20 °C)                                                              |
| Insulation resistance                         | ≥ 10 MΩ*km (at 20 °C)                                                              |
| Nominal voltage, cable                        | 42 V AC                                                                            |
| Test voltage                                  | 1500 V AC                                                                          |
| Minimum bending radius, fixed installation    | 5 x D                                                                              |
| Minimum bending radius, flexible installation | 10 x D                                                                             |
| Smallest bending radius, fixed installation   | 43 mm                                                                              |
| Smallest bending radius, movable installation | 85 mm                                                                              |
| Max. bending cycles                           | 2000000                                                                            |
| Bending radius                                | 85 mm                                                                              |

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

|                                 |                                                                |
|---------------------------------|----------------------------------------------------------------|
| Traversing path                 | 10 m                                                           |
| Traversing rate                 | 3 m/s                                                          |
| Acceleration                    | 10 m/s <sup>2</sup>                                            |
| Flame resistance                | According to DIN EN 60332-1-2                                  |
|                                 | According to VW-1                                              |
| Resistance to oil               | in accordance with DIN EN 60811-2-1                            |
| Other resistance                | hydrolysis and microbe resistant (in accordance with EN 50396) |
| Special properties              | Flexible cable conduit capable                                 |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)                   |
|                                 | -5 °C ... 80 °C (Cable, flexible installation)                 |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Degree of protection            | IP65                                           |
|                                 | IP67                                           |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket)               |
|                                 | -40 °C ... 80 °C (cable, fixed installation)   |
|                                 | -5 °C ... 80 °C (Cable, flexible installation) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable




1430187


<https://www.phoenixcontact.com/us/products/1430187>

## Drawings

Circuit diagram



Dimensional drawing




Socket M12-SPEEDCON, angled, shielded

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable

1430187

<https://www.phoenixcontact.com/us/products/1430187>

Schematic diagram



Pin assignment M12, 12-pos., female side view

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187  
<https://www.phoenixcontact.com/us/products/1430187>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1430187>

|  |                                                |                       |                   |                             |
|--|------------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>UL Listed</b><br>Approval ID: FILE E 221474 |                       |                   |                             |
|  | Nominal voltage $U_N$                          | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 30 V                                           | 1 A                   | -                 | -                           |

|  |                                                      |
|--|------------------------------------------------------|
|  | <b>EAC-RoHS</b><br>Approval ID: RU D-DE.HB35.B.00387 |
|--|------------------------------------------------------|

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187  
<https://www.phoenixcontact.com/us/products/1430187>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## Accessories

### UCT-WMT (23X4) - Conductor marker

0801453

<https://www.phoenixcontact.com/us/products/0801453>



Conductor marker, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 30

---

### UC-WMT (23X4) - Conductor marker

0819411

<https://www.phoenixcontact.com/us/products/0819411>



Conductor marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 24

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## US-WMT (23X4) - Cable marker

0828769

<https://www.phoenixcontact.com/us/products/0828769>



Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 56

---

## WMTW (23X4)R - Cable marker

0831004

<https://www.phoenixcontact.com/us/products/0831004>



Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 3000

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## WP-CTA POM 13,0 BK - Protective hose adapter

1422884

<https://www.phoenixcontact.com/us/products/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

---

## WP-PA HF 13,0 BK - Protective hose

3240681

<https://www.phoenixcontact.com/us/products/3240681>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

## SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

### WP-PA HF-HB 13,0 BK - Protective hose

3240839

<https://www.phoenixcontact.com/us/products/3240839>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

---

### PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>



Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools

---

## B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## CUTFOX-S VDE - Diagonal cutter

1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

---

## WIREFOX SAC-1 - Stripping tool

1212757

<https://www.phoenixcontact.com/us/products/1212757>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/us/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

---

## WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

## TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

# SAC-12P- 5,0-35T/FR SH SCO - Sensor/actuator cable



1430187

<https://www.phoenixcontact.com/us/products/1430187>

## TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

---

## SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)