

1424533

https://www.phoenixcontact.com/us/products/1424533

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 4 mm ... 7 mm, shielding: no, connecting thread: M16 x 1.5, color: lightgrey RAL 7035, with pressure compensation element and flat gasket

Product description

Cable gland with integrated pressure compensation element. Prevents low pressure forming in the housing. Membrane: resistant to water and dirt

Your advantages

- · Reduces the formation of condensation
- · Screw connection with integrated pressure compensation element
- Plastic material conforms to UL 746C f1

Commercial data

Item number	1424533
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF68
Product key	BF7DCX
Catalog page	Page 694 (C-2-2019)
GTIN	4055626374383
Weight per piece (including packing)	7.35 g
Weight per piece (excluding packing)	7.35 g
Customs tariff number	39269097
Country of origin	TR



1424533

https://www.phoenixcontact.com/us/products/1424533

Technical data

Product properties

Product type	Cable screw gland
Application	Standard
No. of conductors	1
Туре	with pressure compensation element and flat gasket
Manufacturer	BIMED
Manufacturer Designation	BMVG-11
Air flow rate	25 (I/h at a pressure differential of 70 mbar)
Shielded	no
Execution of the strain relief	A

Characteristics

Category of shock impact	5
Design, Strain relief	A

Dimensions

Dimensional drawing	19 d) 19 d)
Length	35.5 mm
Length of the connecting thread	10 mm
Hole diameter	16.1 mm 16.2 mm
Wrench size, union nut	19 mm
Wrench size, support	19 mm
Thread type connection side	M16 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	2 Nm ±0.2 Nm (Cap nut)
	2.5 Nm (Support sleeve)

Material specifications

Color	light grey (RAL 7035)
Material	PTFE
Flammability rating according to UL 94	V2
Seal material Flat gasket	NBR
Seal material Cable seal	CR
Material for screw connection	PA

Cable/line



1424533

https://www.phoenixcontact.com/us/products/1424533

External cable diameter Cable 1	4 mm 7 mm
External cable diameter	4 mm 8 mm (for UL 514 B)
Halogen-free	no

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP66
Enclosure rating (NEMA)	1
	4
	4X
	12
	13
Ambient temperature (operation)	-20 °C 100 °C (static)



https://www.phoenixcontact.com/us/products/1424533



Drawings

Dimensional drawing *35,5 10 19 19 19

Dimensional drawing



1424533

https://www.phoenixcontact.com/us/products/1424533

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1424533

DNV

Approval ID: TAE00003WX



cUL Recognized Approval ID: E199260



UL RecognizedApproval ID: E199260

cULus Recognized



1424533

https://www.phoenixcontact.com/us/products/1424533

Classifications

ECLASS

UNSPSC 21.0

	ECLASS-11.0	27144432
	ECLASS-12.0	27140801
	ECLASS-13.0	27140801
ETIM		
	ETIM 9.0	EC000441
UN	SPSC	

39121300



1424533

https://www.phoenixcontact.com/us/products/1424533

Environmental product compliance

REACH candidate substance (CAS No.)

EU RoHS		
Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		

No substance above 0.1 wt%



1424533

https://www.phoenixcontact.com/us/products/1424533

Accessories

A-INL-M16-P-LG - Counter nut

1417660

https://www.phoenixcontact.com/us/products/1417660

Counter nut, for threads M16 x 1.5, color: light grey



SEALING PLUG 6X16 RD - Closing cap

1400254

https://www.phoenixcontact.com/us/products/1400254



Closing cap, color: red

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com