

SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427  
<https://www.phoenixcontact.com/us/products/1682427>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M8, coding: A, on Socket angled M12, coding: A, cable length: 0.3 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1682427                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF03                           |
| Product key                          | BF1CBA                         |
| Catalog page                         | Page 188 (C-2-2019)            |
| GTIN                                 | 4017918159085                  |
| Weight per piece (including packing) | 20.6 g                         |
| Weight per piece (excluding packing) | 17.92 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | DE                             |

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Standard              |
| Number of positions  | 3                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 48 V AC                    |
|                       | 60 V DC                    |
| Nominal current $I_N$ | 4 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|                   | 0.2 Nm (M8 connectors) |

### Connector

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## Connection 1

|                     |                |
|---------------------|----------------|
| Type                | Plug angled M8 |
| Number of positions | 3              |
| Coding type         | A              |

## Connection 2

|                     |                   |
|---------------------|-------------------|
| Type                | Socket angled M12 |
| Number of positions | 3                 |
| Coding type         | A                 |

## Cable/line

|              |       |
|--------------|-------|
| Cable length | 0.3 m |
|--------------|-------|

## PUR halogen-free black [PUR]

|                                 |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|
| Dimensional drawing             |  |
| Cable weight                    | 18 kg/km                                                                            |
| UL AWM Style                    | 20549 / 10493 (80°C/300 V)                                                          |
| Number of positions             | 3                                                                                   |
| Shielded                        | no                                                                                  |
| Cable type                      | PUR halogen-free black [PUR]                                                        |
| Conductor structure signal line | 32x 0.10 mm                                                                         |
| AWG signal line                 | 24                                                                                  |
| Conductor cross section         | 3x 0.25 mm <sup>2</sup> (Signal line)                                               |
| Wire diameter incl. insulation  | 1.17 mm ±0.02 mm                                                                    |
| External cable diameter         | 3.60 mm ±0.15 mm                                                                    |
| Outer sheath, material          | PUR                                                                                 |
| External sheath, color          | black-gray RAL 7021                                                                 |
| Conductor material              | Bare Cu litz wires                                                                  |
| Material wire insulation        | PP                                                                                  |
| Single wire, color              | brown, blue, black                                                                  |
| Thickness, insulation           | ≥ 0.21 mm (Core insulation)                                                         |
| Thickness, outer sheath         | approx. 0.50 mm                                                                     |
| Overall twist                   | 3 wires, twisted                                                                    |
| Length of twist, overall twist  | 40 mm                                                                               |
| Max. conductor resistance       | ≤ 78 Ω/km (at 20 °C)                                                                |
| Insulation resistance           | ≥ 100 GΩ*km (at 20 °C)                                                              |
| Nominal voltage, cable          | ≤ 300 V                                                                             |

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

|                                               |                                                                                                                                                                                           |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test voltage                                  | ≥ 3000 V                                                                                                                                                                                  |
| Smallest bending radius, fixed installation   | 18 mm                                                                                                                                                                                     |
| Smallest bending radius, movable installation | 36 mm                                                                                                                                                                                     |
| Max. bending cycles                           | 10000000                                                                                                                                                                                  |
| Bending radius                                | 44 mm                                                                                                                                                                                     |
| Traversing path                               | 10 m                                                                                                                                                                                      |
| Traversing rate                               | 3 m/s                                                                                                                                                                                     |
| Acceleration                                  | 10 m/s <sup>2</sup>                                                                                                                                                                       |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                                                                                                                                  |
| Flame resistance                              | in accordance with UL 758/1581 FT2<br>DIN EN 60332-2-2 (20 s)                                                                                                                             |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                                                                                                                                       |
| Other resistance                              | hydrolysis and microbe resistant<br>Highly resistant to acids, alkaline solutions and solvents<br>Resistant to salt water<br>partly UV-resistant (in accordance with DIN EN ISO 4892-2-A) |
| Special properties                            | Flexible cable conduit capable<br>Silicone-free<br>Free of substances which would hinder coating with paint or varnish                                                                    |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)<br>-25 °C ... 80 °C (Cable, flexible installation)                                                                                           |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                                                                                                    |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Degree of protection            | IP65<br>IP67<br>IP68                                                                                                               |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket)<br>-40 °C ... 80 °C (cable, fixed installation)<br>-5 °C ... 80 °C (Cable, flexible installation) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |
| Standard designation     | M8 connector    |
| Standards/specifications | IEC 61076-2-104 |


# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable

1682427

<https://www.phoenixcontact.com/us/products/1682427>


## Drawings

Schematic diagram



Layout of connector pin assignments

Dimensional drawing



M8 x 1 male plug, angled version


# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable




1682427

<https://www.phoenixcontact.com/us/products/1682427>

Circuit diagram



Schematic diagram




Pin assignment M12 socket, 3-pos., A-coded, view female side

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable

1682427


<https://www.phoenixcontact.com/us/products/1682427>

Dimensional drawing



M12 x 1 socket, angled

Schematic diagram



Pin assignment M8 plug, 3-pos., view male side

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427  
<https://www.phoenixcontact.com/us/products/1682427>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1682427>

|  |                                                |                                |                   |                               |
|--|------------------------------------------------|--------------------------------|-------------------|-------------------------------|
|  | <b>UL Listed</b><br>Approval ID: FILE E 221474 |                                |                   |                               |
|  | Nominal voltage U <sub>N</sub>                 | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|  | 60 V                                           | 4 A                            | -                 | -                             |

|  |                                                 |                                |                   |                               |
|--|-------------------------------------------------|--------------------------------|-------------------|-------------------------------|
|  | <b>cUL Listed</b><br>Approval ID: FILE E 221474 |                                |                   |                               |
|  | Nominal voltage U <sub>N</sub>                  | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|  | 60 V                                            | 4 A                            | -                 | -                             |

|  |                                                      |  |  |  |
|--|------------------------------------------------------|--|--|--|
|  | <b>EAC-RoHS</b><br>Approval ID: RU D-DE.HB35.B.00387 |  |  |  |
|  |                                                      |  |  |  |

|                     |  |  |  |  |
|---------------------|--|--|--|--|
| <b>cULus Listed</b> |  |  |  |  |
|---------------------|--|--|--|--|

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427  
<https://www.phoenixcontact.com/us/products/1682427>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## Accessories

### PROT-M 8 FS-PA-CHAIN - Sealing cap

1430857

<https://www.phoenixcontact.com/us/products/1430857>

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



### UCT-WMT (23X4) - Conductor marker

0801453

<https://www.phoenixcontact.com/us/products/0801453>



Conductor marker, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 30

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## UC-WMT (23X4) - Conductor marker

0819411

<https://www.phoenixcontact.com/us/products/0819411>



Conductor marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 24

---

## US-WMT (23X4) - Cable marker

0828769

<https://www.phoenixcontact.com/us/products/0828769>



Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 56

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## WMTW (23X4)R - Cable marker

0831004

<https://www.phoenixcontact.com/us/products/0831004>



Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 3000

---

## PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>



Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools

---

## B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## TSD 02 SAC - Torque screwdriver

1208487

<https://www.phoenixcontact.com/us/products/1208487>



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

---

## SAC BIT M8-D10 - Tool

1208461

<https://www.phoenixcontact.com/us/products/1208461>



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

## TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

# SAC-3P-M 8MR/0,3-PUR/M12FR - Sensor/actuator cable



1682427

<https://www.phoenixcontact.com/us/products/1682427>

## TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

---

## SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)