2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



V8 adapter for 8 x PLC-INTERFACE (6.2 mm), controller: PLC system cabling of input cards, connection 1: D-SUB socket strip 1x 15-position, connection 2: Plug-in connection (Can be snapped onto 8x PLC-INTERFACE terminals), connection 3: Screw connection 1x 2-position, number of channels: 8, control logic: positive switching

Commercial data

Item number	2296087
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C421
Product key	CK21D2
Catalog page	Page 427 (C-5-2019)
GTIN	4017918189136
Weight per piece (including packing)	110.68 g
Weight per piece (excluding packing)	110.68 g
Customs tariff number	85369010
Country of origin	DE



2296087

https://www.phoenixcontact.com/us/products/2296087

Technical data

Product properties

	Late free word to
Product type	Interface module
Product family	PLC-INTERFACE
Number of positions	15
No. of channels	8
nsulation characteristics	
Insulation	Functional insulation
nsulation characteristics: Air clearances and creepage distances	
Insulation	Functional insulation
Overvoltage category	Ш
Pollution degree	2
ectrical properties	
Operating voltage range	18 V DC 33.6 V DC
	18 V DC 33.6 V DC ≤ 1 A
Operating voltage range	
Operating voltage range Current (per branch)	≤ 1 A
Operating voltage range Current (per branch) Current (Power supply)	≤ 1 A
Operating voltage range Current (per branch) Current (Power supply) Air clearances and creepage distances	≤ 1 A ≤ 3 A
Operating voltage range Current (per branch) Current (Power supply) Air clearances and creepage distances Rated insulation voltage	≤ 1 A ≤ 3 A 50 V
Operating voltage range Current (per branch) Current (Power supply) Air clearances and creepage distances Rated insulation voltage Rated surge voltage	≤ 1 A ≤ 3 A 50 V

Connection 1 (control level)			
Connection in acc. with standard	IEC 60807-2		
Connection method D-SUB socket strip			
Screw thread	UNC 4-40		
Number of connections	1		
Number of positions 15			
Insertion/withdrawal cycles > 500			
Pitch	2.74 mm		
Connection 2 (field level)			
Connection method	Plug-in connection		
Note	Can be snapped onto 8x PLC-INTERFACE terminals		

Connection 3 (supply)

Connection method	Screw connection
Stripping length	8 mm



2296087

https://www.phoenixcontact.com/us/products/2296087

Screw thread	M3	
Number of connections	1	
Number of positions	2	
Conductor cross section rigid	0.2 mm ² 4 mm ²	
Conductor cross-section rigid (2 conductors with same cross section)	0.2 mm ² 1.5 mm ²	
Conductor cross section flexible	0.2 mm² 2.5 mm²	
	0.25 mm ² 2.5 mm ² (Ferrule without plastic sleeve)	
	0.25 mm ² 2.5 mm ² (Ferrule with plastic sleeve)	
Conductor cross section flexible (2 conductors with same cross	0.2 mm² 1.5 mm²	
section)	0.25 mm ² 0.75 mm ² (Ferrule without plastic sleeve)	
	0.5 mm ² 1.5 mm ² (TWIN ferrule with plastic sleeve)	
Conductor cross section AWG	24 12	
Tightening torque	0.5 Nm 0.6 Nm	
Pitch	5 mm	

Signaling

Status display present	Yes
Operating voltage display	Green LED

Dimensions

Item dimensions

Width	49.93 mm
Height	41 mm
Depth	49.81 mm

Material specifications

Color	gray (RAL 7042)	
Flammability rating according to UL 94	V0	
Housing insulation material	Polyamide 6.6 green	

Environmental and real-life conditions

Ambient conditions	
Degree of protection (Module)	IP20
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-40 °C 70 °C
Ambient temperature (storage/transport)	-40 °C 70 °C
Altitude	≤ 2000 m

Approvals

CE	
Certificate	CE-compliant

UKCA



https://www.phoenixcontact.com/us/products/2296087

UKCA-compliant Class I, Div. 2, Groups A, B, C, D T4 Class I, Zone 2, Ex ec IIC Gc T4 X Class I, Zone 2, AEx ec IIC T4 Class I, Zone 2, AEx ec IIC T4 TAE0000196 D A C
Class I, Zone 2, Ex ec IIC Gc T4 X Class I, Zone 2, AEx ec IIC T4 TAE0000196 D A
Class I, Zone 2, Ex ec IIC Gc T4 X Class I, Zone 2, AEx ec IIC T4 TAE0000196 D A
Class I, Zone 2, AEx ec IIC T4 TAE0000196 D A
Class I, Zone 2, AEx ec IIC T4 TAE0000196 D A
D A
D A
D A
D A
A
A
A
В
Required protection according to the Rules shall be provided upon installation on board
Conformance with Low Voltage Directive
Conformance with EMC directive
EN IEC 60664-1
Plug-on assembly
in rows with zero spacing
any
For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third- party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also


PHŒNIX CONTACT



2296087

https://www.phoenixcontact.com/us/products/2296087

Drawings





2296087

https://www.phoenixcontact.com/us/products/2296087

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2296087

		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		24 V	1 A	-	-
	UL Recognized Approval ID: FILE E 2387(25			
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		24 V	1 A	-	-
		24 V		-	-
)	DNV GL Approval ID: TAE0000196				
	UL Listed Approval ID: FILE E 172140				
?	CUL Listed Approval ID: FILE E 172140)			
)	cUL Listed Approval ID: FILE E 199827	,			
	UL Listed Approval ID: FILE E 199827				
cl	JLus Recognized				
cl	JLus Listed				



https://www.phoenixcontact.com/us/products/2296087



Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-12.0	27141152
ECLASS-13.0	27141152

ETIM

	ETIM 9.0	EC002780
UNSPSC		
	UNSPSC 21.0	39121400



https://www.phoenixcontact.com/us/products/2296087



Environmental product compliance

Yes
6(c)
EFUP-50
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
Hexahydromethylphthalic anhydride(CAS: n/a)
Lead(CAS: 7439-92-1)

2296087

https://www.phoenixcontact.com/us/products/2296087



Mandatory accessories

PLC-RPT- 12DC/21AU - Relay Module

2900317 https://www.phoenixcontact.com/us/products/2900317



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 12 V DC

PLC-RSC- 12DC/21AU - Relay Module

2966919

https://www.phoenixcontact.com/us/products/2966919



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 12 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-RPT- 24DC/21AU - Relay Module

2900306

https://www.phoenixcontact.com/us/products/2900306



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 24 V DC

PLC-RSC- 24DC/21AU - Relay Module

2966265

https://www.phoenixcontact.com/us/products/2966265



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 24 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-RPT- 24UC/21AU - Relay Module

2900307

https://www.phoenixcontact.com/us/products/2900307



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 24 V AC/DC

PLC-RSC- 24UC/21AU - Relay Module

2966278 https://www.phoenixcontact.com/us/products/2966278



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 24 V AC/DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-RPT- 48DC/21AU - Relay Module

2900308

https://www.phoenixcontact.com/us/products/2900308



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 48 V DC

PLC-RSC- 48DC/21AU - Relay Module

2966126 https://www.phoenixcontact.com/us/products/2966126



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 48 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-RPT- 60DC/21AU - Relay Module

2900309

https://www.phoenixcontact.com/us/products/2900309



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 60 V DC

PLC-RSC- 60DC/21AU - Relay Module

2966142 https://www.phoenixcontact.com/us/products/2966142



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 60 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACT

PLC-RPT-120UC/21AU - Relay Module

2900310

https://www.phoenixcontact.com/us/products/2900310



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 120 V AC/110 V DC

PLC-RSC-120UC/21AU - Relay Module

2966281 https://www.phoenixcontact.com/us/products/2966281



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 120 V AC/110 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-RPT-230UC/21AU - Relay Module

2900311

https://www.phoenixcontact.com/us/products/2900311



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 230 V AC/220 V DC

PLC-RSC-230UC/21AU - Relay Module

2966294

https://www.phoenixcontact.com/us/products/2966294



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 230 V AC/220 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-BPT-120UC/21/SO46 - Relay base

2900453

https://www.phoenixcontact.com/us/products/2900453



6.2 mm PLC basic terminal block against interference currents/voltages on the control side with Push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with integrated RCZ filter, 1 changeover contact, input voltage 120 V AC

PLC-BSC-120UC/21/SO46 - Relay base

2980319 https://www.phoenixcontact.com/us/products/2980319



6.2 mm PLC basic terminal block with protection against interference currents/voltages on the control side, with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with integrated RCZ filter, 1 changeover contact, input voltage 120 V AC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-BPT-230UC/21/SO46 - Relay base

2900455

https://www.phoenixcontact.com/us/products/2900455



6.2 mm PLC basic terminal block against interference currents/voltages on the control side with Push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with integrated RCZ filter, 1 changeover contact, input voltage 230 V AC

PLC-BSC-230UC/21/SO46 - Relay base

2980335

https://www.phoenixcontact.com/us/products/2980335



6.2 mm PLC basic terminal block with protection against interference currents/voltages on the control side, with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with integrated RCZ filter, 1 changeover contact, input voltage 230 V AC

2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACT

PLC-OPT- 24DC/ 48DC/100 - Solid-state relay module

2900352

https://www.phoenixcontact.com/us/products/2900352



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 24 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC- 24DC/ 48DC/100 - Solid-state relay module

2966728

https://www.phoenixcontact.com/us/products/2966728



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 24 V DC, output: 3 - 48 V DC/100 mA

2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACT

PLC-OPT- 48DC/ 48DC/100 - Solid-state relay module

2900353

https://www.phoenixcontact.com/us/products/2900353



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 48 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC- 48DC/ 48DC/100 - Solid-state relay module

2966993

https://www.phoenixcontact.com/us/products/2966993



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 48 V DC, output: 3 - 48 V DC/100 mA

2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACT

PLC-OPT- 60DC/ 48DC/100 - Solid-state relay module

2900354

https://www.phoenixcontact.com/us/products/2900354



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 60 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC- 60DC/ 48DC/100 - Solid-state relay module

2967455

https://www.phoenixcontact.com/us/products/2967455



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 60 V DC, output: 3 - 48 V DC/100 mA

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-OPT-120UC/ 48DC/100 - Solid-state relay module

2900355

https://www.phoenixcontact.com/us/products/2900355



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 120 V AC/110 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC-120UC/ 48DC/100 - Solid-state relay module

2966744

https://www.phoenixcontact.com/us/products/2966744



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 120 V AC/110 V DC, output: 3 - 48 V DC/100 mA

HŒR

2296087

https://www.phoenixcontact.com/us/products/2296087

PHŒNIX CONTACI

PLC-OPT-230UC/ 48DC/100 - Solid-state relay module

2900356

https://www.phoenixcontact.com/us/products/2900356



PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 230 V AC/220 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC-230UC/ 48DC/100 - Solid-state relay module

2966757

https://www.phoenixcontact.com/us/products/2966757



PLC-INTERFACE, consisting of PLC-BSC.../21 basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 230 V AC/220 V DC, output: 3 - 48 V DC/100 mA

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-PT-EIK 1-SVN 24P/P - Solid-state relay module

2900397

https://www.phoenixcontact.com/us/products/2900397



PLC-INTERFACE for NAMUR applications, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and integrated circuit, for mounting on NS 35/7,5 DIN rail, positive switching output, 24 V DC supply voltage

PLC-SC-EIK 1-SVN 24P/P - Solid-state relay module

2982663

https://www.phoenixcontact.com/us/products/2982663



PLC-INTERFACE for NAMUR applications, consisting of PLC-BSC.../21 basic terminal block with screw connection and integrated circuit, for mounting on NS 35/7,5 DIN rail, positive switching output, 24 V DC supply voltage

2296087

https://www.phoenixcontact.com/us/products/2296087

DPHŒNIX CONTACI

PLC-VT - Feed-through terminal block

2296870

https://www.phoenixcontact.com/us/products/2296870



VARIOFACE feed-through terminal block (2-conductor screw connection), for PLC-INTERFACE universal series

PLC-VT/LA - Feed-through terminal block

2296854

https://www.phoenixcontact.com/us/products/2296854



VARIOFACE feed-through terminal block (2-conductor screw connection), for PLC-INTERFACE universal series, with 24 V DC LED display

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-RPT- 24DC/ 1AU/SEN - Relay Module

2900313

https://www.phoenixcontact.com/us/products/2900313



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 24 V DC

PLC-RSC- 24DC/ 1AU/SEN - Relay Module

2966317 https://www.phoenixcontact.com/us/products/2966317



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 24 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-RPT-120UC/ 1AU/SEN - Relay Module

2900314

https://www.phoenixcontact.com/us/products/2900314



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 120 V AC/110 V DC

PLC-RSC-120UC/ 1AU/SEN - Relay Module

2966320

https://www.phoenixcontact.com/us/products/2966320



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 120 V AC/110 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-RPT-230UC/ 1AU/SEN - Relay Module

2900315

https://www.phoenixcontact.com/us/products/2900315



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 230 V AC/220 V DC

PLC-RSC-230UC/ 1AU/SEN - Relay Module

2966333

https://www.phoenixcontact.com/us/products/2966333



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 230 V AC/220 V DC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-BPT-120UC/ 1/SEN/SO46 - Relay base

2900456

https://www.phoenixcontact.com/us/products/2900456



6.2 mm PLC basic terminal block with interference current and interference voltage protection on the control side, with push-in connection, without relay or solid-state relay, with sensor supply voltage distribution (BB), 1 N/O contact, input voltage 120 V AC

PLC-BSC-120UC/ 1/SEN/SO46 - Relay base

2980322

https://www.phoenixcontact.com/us/products/2980322



6.2 mm PLC basic terminal block with interference current and interference voltage protection on the control side, with screw connection, without relay or solid-state relay, with sensor supply voltage distribution (BB), 1 N/O contact, input voltage 120 V AC

2296087

https://www.phoenixcontact.com/us/products/2296087



PLC-BPT-230UC/ 1/SEN/SO46 - Relay base

2900457

https://www.phoenixcontact.com/us/products/2900457



6.2 mm PLC basic terminal block with interference current and interference voltage protection on the control side, with push-in connection, without relay or solid-state relay, with sensor supply voltage distribution (BB), 1 N/O contact, input voltage 230 V AC

PLC-BSC-230UC/ 1/SEN/SO46 - Relay base

2980348

https://www.phoenixcontact.com/us/products/2980348



6.2 mm PLC basic terminal block with interference current and interference voltage protection on the control side, with screw connection, without relay or solid-state relay, with sensor supply voltage distribution (BB), 1 N/O contact, input voltage 230 V AC

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-OPT- 24DC/ 48DC/100/SEN - Solid-state relay module

2900358

https://www.phoenixcontact.com/us/products/2900358



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 24 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC- 24DC/ 48DC/100/SEN - Solid-state relay module

2966773

https://www.phoenixcontact.com/us/products/2966773



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 24 V DC, output: 3 - 48 V DC/100 mA

HŒR

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-OPT-120UC/ 48DC/100/SEN - Solid-state relay module

2900359

https://www.phoenixcontact.com/us/products/2900359



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 120 V AC/110 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC-120UC/ 48DC/100/SEN - Solid-state relay module

2966799

https://www.phoenixcontact.com/us/products/2966799



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 120 V AC/110 V DC, output: 3 - 48 V DC/100 mA

HŒR

2296087

https://www.phoenixcontact.com/us/products/2296087

PLC-OPT-230UC/ 48DC/100/SEN - Solid-state relay module

2900361

https://www.phoenixcontact.com/us/products/2900361



PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 230 V AC/220 V DC, output: 3 - 48 V DC/100 mA

PLC-OSC-230UC/ 48DC/100/SEN - Solid-state relay module

2966809

https://www.phoenixcontact.com/us/products/2966809



PLC-INTERFACE for input functions, consisting of PLC-BSC.../SEN basic terminal block with screw connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 230 V AC/220 V DC, output: 3 - 48 V DC/100 mA

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com - (OE 1