DATA SHEET

COAXIAL FIXED ATTENUATOR, 50 Ohm, 6 dB, N

5906_N-50-1/133_N

Properties

- Wide range of interfaces
- Fixed attenuation level from 0 dB up to 40 dB
- 50 Ω or 75 Ω impedance
- Various bandwidth to improve the impedance matching between subsystems of its waveform
- Used in many test and measurement and communication applications.



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 6 GHz
Attenuation nominal	6 dB
VSWR	1.25
Return loss	19.1 dB

Electrical Data (frequency related)		
Frequency range	**Attenuation deviation**	**VSWR max**
0 GHz to 6 GHz	+/- 0.8 dB	1.25

Electrical Data (power)	
Average power	100 W at 25 °C ambient temperature. Linearly derated to 10 W at 100 °C ambient temperature.
Peak power	5000 W, 5 µs pulse width, 0.5 % duty cycle

COAXIAL FIXED ATTENUATOR, 50 Ohm, 6 dB, N

5906_N-50-1/133_N

Interface and material data		
Interface	N / plug (male)	
Piece parts	**Material**	**Plating**
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Stainless Steel	Passivated (Plating)
Interface	N / jack (female)	
Piece parts	**Material**	**Plating**
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	

Mechanical data	
Weight	1.45 kg

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table	
Item number	Item description
85177209	5906_N-50-1/133_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1845 / Date of publication: 23.11.2023 / uncontrolled copy