

SERVICE ENTRANCE SUPPRESSOR(P), 40 KA DC, 300 VDC UN

CATALOG NUMBER

SES40P300DC



CERTIFICATIONS



FEATURES

Compact NEMA®-4X enclosure design can be flush mounted or installed in a small space

40 kA 8/20 µs maximum surge rating provides protection suitable for service entrance and distribution panels

Mounting bracket available for mounting within panel backplane

PRODUCT ATTRIBUTES

Nominal System Voltage (Un): 300 VDC

Distribution System: DC 2W+G

Max Continuous Operating Voltage (Uc): 360 VDC

Short Circuit Current Rating (SCCR): 100 kA

Nominal Discharge Current (In): 20 kA 8/20 µs

Max Discharge Current (Imax): 40 kA 8/20 µs

Voltage Protection Rating (VPR): 1200 V @ 3 kA

Voltage Protection Rating (VPR), DC+ - DC-: 2500 V

Voltage Protection Rating (VPR), PE - DC+: 1500 V

Voltage Protection Rating (VPR), PE - DC-: 1500 V


Status Indication: Blue LED

Technology: MOV with thermal disconnect

Lead Length: 30

Lead Size imperial: #12
Temperature: -40 to 176 °F
Enclosure Material: UL® 94V-0 Thermoplastic
Enclosure Rating: NEMA®-4X
Mounting: 3/4" straight nipple
Unit Weight: 0.55 lb
Certification Details: UL® 1449 Edition 5 for DC General Use
Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C
Depth: 3"
Height: 2 3/4"
Width: 4 3/4"

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--