

FTCBI INSULATED FLAT BRAID IN COIL, TINNED COPPER, 250 A, 98.68 KCMIL, 82'

CATALOG NUMBER

FTCBI50



CERTIFICATIONS



FEATURES

Braids in coil are mainly used for power distribution or earthing applications

Non-magnetic material

Tinned finish provides a theft-deterrent appearance

PRODUCT ATTRIBUTES

Article Number: 510340

Material: Copper;Polyvinylchloride

Finish: Tinned

Nominal Current: 250 A

Cross Section: 98.68 kcmil

Number of Wires: 2848

Wire Diameter: 0.01

Length: 82'

Thickness: 0.2"

Width: 1.2"

Unit Weight: 1.32 lb

Insulation Thickness: 0.04"

Insulation Voltage: 450 V

Temperature: 158 °F Max

Flammability Rating: UL® 94V-0

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER