

Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


Body





Protector





Clamp














A-A (5:1)



B-B (5:1)



Assembly figure



HRS DRAWING FOR REFERENCE

Notes 1 The dimensions in parentheses are for reference.
△1 2 Once a connector is harnessed, the connector shall not be re-harnessed to a different cable.
Protectors and clamps shall also not be re-used once used in assembly.
When repair is needed, please replace the connector as well as all connector parts.

Re-using connector and connector parts may cause continuity failure due to
contact deformation / breakage, lock part destruction, etc.
△2 3 UL(File No.E52653)
C-UL(File No.E52653) authorization article. cULus

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
1	BERYLLIUM COPPER	Contact area : Gold 0.2μm min.	4	PBT	BLACK UL94V-0
		Other area : Gold 0.03μm min.	3	PBT	BLACK UL94V-0
		Under plating : Nickel	2	PBT	BLACK UL94V-0

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	1 : 1	△2	1	DIS-F-00005872	AK. IWAHORI	HT. YAMAGUCHI	20200221

HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	20181211
CHECKED	HT. YAMAGUCHI	20181211
DESIGNED	MT. ITANO	20181211
DRAWN	MK. OOKI	20181207

DRAWING NO.	EDC-017345-63-00
PART NO.	HIF3BA-64D-2.54R(63)
CODE NO.	CL610-0031-0-63 △2 1/1