1-1564559-1 ✔ ACTIVE

MCON Interconnection System

TE Internal #: 1-1564559-1

Housing for Male Terminals, Wire-to-Wire, 4 Position, .157 in [4 mm] Centerline, Sealable, Black, Wire & Cable, Power, MCON Interconnection System

View on TE.com >

Connectors > Automotive Connectors > Automotive Housings



Connector System: **Wire-to-Wire**

Number of Positions: **4**

Connector & Housing Type: **Housing for Male Terminals**

Centerline (Pitch): **4 mm [.157 in]**

Sealable: **Yes**

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	14 VDC
Nominal Voltage Architecture	12 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A

Contact Features

Contact Size	1.2mm
Contact Type	Tab
Contact Current Rating (Max)	25 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Connector Height	16.3 mm[.642 in]
Product Width	44 mm[1.732 in]
Product Length	24.2 mm[.953 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]

Operation/Application

Circuit Application	Power

Packaging Features

Packaging Quantity	1000
Packaging Method	Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1718645-1
4POS, MCON 1.2 LL REC SEALED



TE Part # 1-1670918-1
4POS, MCON 1.2 LL REC SEALED



TE Part # 967056-1
MQS BLINDSTOPFEN4MM



TE Part # 967067-1
MQS SGL WIRE SEAL



TE Part # 967067-2
MQS EINZELLEITDICHT



TE Part # CAT-M4595-T273
MCON Receptacle and Tab



TE Part # CAT-M4596-CH8172
HPF 1.2, CONNECTOR HOUSING



TE Part # 3-1579028-8
EXTRACTION TOOL



TE Part # 3-1579028-5
TOOL FOR SECONDARY LOCK

TE Part # 1-1564560-1
4POS,TAB 1.2X0.6,TAB HSG,SWS



TE Part # 1-2378604-1
4POS,NEXTGEN, MCON 1.2 LL REC, SLD,COD A

TE Part # 1564561-1
RETAINER,4-POS. MALE-HSG.



TE Part # 1718761-3
MCON 1.2 LL TAB SWS AG LP

Also in the Series | MCON Interconnection System



Automotive Connector Caps & Covers (21)



Automotive Connector Locks & Position Assurance(11)



Automotive Housings(288)



Automotive Terminals(104)



Connector Seals & Cavity Plugs(11)



Insertion & Extraction Tools(31)



Other Automotive Connector Accessories(2)



PCB Headers & Receptacles(2)

Customers Also Bought



TE Part # 9-1670068-9
48POS MIXED MQS REC SEALED COD 1



TE Part # 184344-1
2X2 PLG ASY KEY A C3



TE Part # 2-1564559-1
4POS, MCON 1.2 LL TAB SEALED COD B



TE Part # 2-2236896-1
2POS, MCON 1.2 LL REC SEALED



TE Part # 2337311-1
2X2 PLG ASY KEY H C3 W/CPA



TE Part # 3-2236896-1
2POS, MCON 1.2 LL REC SEALED



TE Part # 5-1719105-1
14POS,JPT,REC.HSG,BK

TE Part # 2311425-1
EVC135 CABLE ASSY

TE Part # 2374558-1
FUSE_40A

TE Part # 2393902-1
PDU ASSY,NPC PLATFORM PDU

Documents

Product Drawings

4POS, MCON 1.2 LL TAB SEALED COD A

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1564559-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1564559-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1564559-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

MCON Interconnection System

English

Product Specifications

Application Specification

English