

KISSLING | KISSLING Series 29

TE Internal #: K1060611

Power Relays, Standard, Monostable, 10 mW Coil Power Rating DC, 62 Ω Coil Resistance, Coil Suppression Diode, KISSLING Series 29

View on TE.com >



Relays & Contactors > Relays > Power Relays > Power Relay, 300A, Standard, Monostable, DC



Relay Type: Standard

Coil Magnetic System: Monostable
Coil Power Rating DC: 10 mW

Coil Resistance: 62 Ω

Coil Special Features: Coil Suppression Diode

All Power Relay, 300A, Standard, Monostable, DC (22)

Features

Product Type Features

Product Type Features	
Relay Type	Standard
Configuration Features	
Coil Special Features	Coil Suppression Diode
Contact Arrangement	1 Form X (SPST-NO-DM)
Contact Number of Poles	1
Electrical Characteristics	
Coil Power Rating DC	10 mW
Coil Resistance	62 Ω
Coil Voltage Rating	18 VDC, 32 VDC
Contact Current Rating	300 A
Contact Voltage Rating	28 VDC
Contact Features	
Contact Material	AgSnO2
Termination Features	
Relay Connection Type	Terminals

Screw Terminals

Terminal Configuration



Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis
Dimensions	
Product Width	62 mm[2.44 in]
Product Length	120 mm[4.72 in]
Product Height	55.5 mm[2.18 in]
Operation/Application	
Actuating System	DC
Coil Magnetic System	Monostable
Other	
Contact Current Class	300 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (92.5% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # CAT-AL6-KSPR29300 Power Relay, 300A, Standard, Monostable, DC




TE Part # CAT-AL6-KSPR30300 Power Relay, 300A, Standard, Bistable, 2 Coils, Polarized



TE Part # K1023465 Relay 29-314-12-903



Also in the Series | KISSLING Series 29




Customers Also Bought





TE Part # 5069724010 CGPT-6.4/3.2-X-SP



TE Part # CB03314003 RW-200-E-3/16-0-SP











Documents

Product Drawings



Relay 29-311-12A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_29-311-12A_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_29-311-12A_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_29-311-12A_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

KISSLING SINGLE POLE POWER RELAYS Series 29 / 300A

English