



HPI

TE Internal #: 1-1775441-3

Housing, Receptacle, Wire-to-Wire, 13 Position, .059 in [1.5 mm]


Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable,

HPI

[View on TE.com >](#)

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings >

AMP HPI 1.5 mm Receptacle Housings



Connector Product Type: **Housing**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Wire**

Number of Positions: **13**

Centerline (Pitch): **1.5 mm [.059 in]**

[All AMP HPI 1.5 mm Receptacle Housings \(15\)](#)

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	13
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

--	--



Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Layout	Inline
Contact Type	Socket
Contact Current Rating (Max)	3 A

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Strain Relief	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Lock
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Entry Configuration	Both Ends Closed
Housing Material	Thermoplastic
Centerline (Pitch)	1.5 mm[.059 in]

Dimensions

Connector Length	20.6 mm[.811 in]
Connector Height	2.7 mm[.106 in]
Connector Width	6.15 mm[.245 in]
Wire Size	.05 - .02 mm ²

Usage Conditions

Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1000
--------------------	------



Packaging Method

Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1775442-1
EMIX CONN., 1.5mm PITCH, TERMI

TE Part # CAT-H857-H34215
AMP HPI 1.5 mm Headers

Also in the Series | HPI



Connector Contacts(1)



PCB Headers & Receptacles(332)




Wire-to-Board Connector Assemblies & Housings(134)


Customers Also Bought




TE Part # 172061-3
DRAWER CONN 12P MALE



TE Part # 3-1623789-2
SQM7 330R 5% (WIRE)



TE Part # 1-2307817-0
10P,2MM,BB,REC,DRV,T,SMD,0.1AU,TR,W/CP



TE Part # 2342839-1
AVP19M FLAT AIO RGB R 500MM/1X6



TE Part # 4-173977-7
CT CONN MT REC ASSY 7P YELLOW



TE Part # 72350000-000
GCT-121-250




TE Part # 1-1627024-1
H1191/R2500



TE Part # 1-103648-9
20 MTE RCPT HSG SR RIB .100CL



TE Part # 2271284-1
DUST CAP FOR ENCODER



TE Part # 2-643075-3
23P MTA100 MOLDED COVER

Documents

Product Drawings

EMIX CONN., 1.5MM PITCH, RCPT, HSG, 13P

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1775441-3_B.2d_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_1-1775441-3_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-1775441-3_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[HPI Connectors QRG](#)

English

Product Specifications

[Application Specification](#)

English