SIEMENS

Data sheet 6XV1830-5EH10

product description	Bus cable (2-core), sold by the meter, unassembled
	PB FC Process Cable GP/ Ethernet-APL cable GP, bus cable for IEC 61158-2 (PB) and IEC TS 60079-47 (2-WISE) sheath color blue for Ex applications 2-core shielded, sold by the meter delivery unit max. 1000 m minimum order quantity 20 m.



suitability for use	Use in fieldbus systems according to IEC 61158-2 (e.g. PROFIBUS PA) and IEC TS 60079-47 (2-WISE) / for APL (cable type A), suitable for Ex applications
cable designation	02YSY (ST) CY 1x2x1,0/2,55-100 BL OE FR
electrical data	
attenuation factor per length	
● at 38.4 kHz / maximum	0.003 dB/m
return loss	
● at 3 MHz	19 dB
impedance	
● rated value	100 Ω
● at 31.25 kHz	100 Ω
● at 3 MHz … 20 MHz	100 Ω
relative symmetrical tolerance	
● of the characteristic impedance at 31.25 kHz	20 %
● of the characteristic impedance at 3 MHz … 20 MHz	15 %
loop resistance per length / maximum	44 mΩ/m
shield resistance per length / maximum	6.5 Ω/km
capacity per length / at 1 kHz	92 pF/m
inductance per length	0.65 µH/m
operating voltage	
● RMS value	80 V
mechanical data	
number of electrical cores	2
design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
type of electrical connection / FastConnect	Yes
outer diameter	
● of inner conductor	1.05 mm
● of the wire insulation	2.55 mm
● of the inner sheath of the cable	5.4 mm
● of cable sheath	8 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.4 mm
material	
● of the wire insulation	polyethylene (PE)
● of the inner sheath of the cable	PVC
● of cable sheath	PVC
color	
● of the insulation of data wires	red/green
● of cable sheath	blue
bending radius	

Subject to change without notice
© Copyright Siemens

● with single bend / minimum permissible	40 mm
● with multiple bends / minimum permissible	80 mm
tensile load / maximum	150 N
weight per length	103 kg/km
ambient conditions	
ambient temperature	
● during operation	-40 ... +80 °C
● during storage	-40 ... +80 °C
● during transport	-40 ... +80 °C
● during installation	-20 ... +80 °C
● note	Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472
ambient condition / for operation	Transfer rate of cable: 31.25 Kbit/s
fire behavior	flame resistant according to IEC 60332-3-24 (Category C)
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
● to mineral oil	conditional resistance
● to grease	Conditional resistance
● to water	conditional resistance
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
● halogen-free	No
● silicon-free	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; c(UL)us, CMG / CL3 / Sun Res
UL/ETL style / 600 V Rating	Yes
certificate of suitability	
● EAC approval	Yes
● CE marking	Yes
● RoHS conformity	Yes
product conformity	
● IEC TS 60079-47 (2-WISE) / for APL (cable type A)	Yes
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Germanische Lloyd (GL)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
reference code	
● according to IEC 81346-2	WG
● according to IEC 81346-2:2019	WGB
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 7/7/2022

Subject to change without notice
© Copyright Siemens