

## AX104687 Faceplates and Panels - KeyConnect Tamper Resist Faceplate 4-port w/ lock cover, seal and gasket Single-Gang



For more Information  
please call

1-800-Belden1



### General Description:

KeyConnect Tamper Resistant Faceplate 4-port w/ lock cover, seal and gasket, Single-Gang

### Usage (Overall)

<b>Suitable Applications:</b>	Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400, 1200, fiber and coax.
<b>Related Parts:</b>	Compatible with KeyConnect-style Modular jacks 10GX, CAT6+, CAT5E and KeyConnect-style Fiber and Coax Connectors. Note that the use of ST fiber patchcord may result in high IL value.

### Physical Characteristics (Connectivity)

#### Capacity

<b>Max. Capacity:</b>	4 ports
-----------------------	---------

#### Access

<b>Front Connection:</b>	Recessed
--------------------------	----------

#### Dimensions

##### Dimensions:

Height (in.)	Width (in.)	Depth (in.)
4.880	2.980	2.090

#### Materials

##### Materials:

Description	Material
Backplate and Cover	Plastic - UL94V-0
Grommet and Gasket	Silicone - UL94V-0

#### Color

<b>Color:</b>	Creamy white
---------------	--------------

#### Weight

<b>Weight:</b>	0.310 lbs.
----------------	------------

#### Included Parts

<b>Included Parts:</b>	(2) #6-32 mounting screws, (2) #6-32 cover std screws and (2) #6-32 cover tamper resistant screws, cover, seal, gasket, (2) blanks, installation guide
------------------------	--

#### Packaging

<b>Packaging:</b>	Individually packaged in a suitable plastic bag
-------------------	---

### Mechanical Characteristics (Connectivity)

<b>Storage Temperature Range:</b>	-40°C To +70°C
<b>Installation Temperature Range:</b>	-10°C To +60°C
<b>Operating Temperature Range:</b>	-10°C To +60°C

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	07/01/2006
<b>MII Order #39 (China RoHS):</b>	Yes
<b>Safety Listing:</b>	Bi-national Standard Listed

#### Suitability

<b>Suitability - Indoor:</b>	Yes
------------------------------	-----

### Transmission Characteristics (Connectivity)

### Notes (Overall)

**Notes:** For proper installation refer to Installation Guide PX105690-EN included with the product or visit our web site at <http://www.belden.com>

## ENGLISH MEASUREMENT VERSION

### AX104687 Faceplates and Panels - KeyConnect Tamper Resist Faceplate 4-port w/ lock cover, seal and gasket Single-Gang

**Notes (Cont'd.):**

Spanner insert bit for #6-32 screw, product number AX104689, must be bought to use tamper resistant screw.

**Product Family**

**Part Numbers:**

Description	Part Number
KeyConnect Tamper Resist Faceplate 4-port w/ lock cover, seal and gasket Single-Gang	AX104687
KeyConnect Tamper Resist Faceplate 4-port w/ lock cover, Single-Gang	AX104688
KeyConnect Spanner insert bit for #6-32 screw	AX104689

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX104687	1 EA	0.000 KG			KCONN Tamper Resist FP, 4p,WH

Revision Number: 0 Revision Date: 11-11-2013

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.