



Product: FX Brilliance 250 um Boot ☑

FX Brilliance Universal 250µm Boot, 25/Pack

Product Description

FX Brilliance Universal 250µm Boot, Black, 25/Pack

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	Field-termination of fiber optic cables within Patch Panels, Distribution Frames, Workstation Outlets for FTTD (Fiber to the Desk), drops for FTTH (Fiber to the home) and MDU (Multiple Dwelling Units).

Construction

Weight: 0.020 kg

Mechanical Characteristics

Termination Style:	Mechanical
,	

Standards

TIA/EIA Compliance:	TIA 568.3-D
EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	EUP 50
Safety Listing:	ACA

Related Part Numbers

Related Parts:	FX Brilliance Precision Installation Kit, FX Brilliance Universal Connectors

Variants

ltem #	Color	Packaging	UPC
FXBUBO250B25N	Black	Twenty-five (25) boots in bag.	611589165525

Product Notes

Packaging:	Twenty-five (25) boots in bag.	
Notes:	Refer to Installation Guide PX105234 for installation procedures	

History

Update and Revision:	Revision Number: 0.61 Revision Date: 03-04-2023

© 2023 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.