# Data sheet

## 2796.0 HZL/1,0 HL-D RD

Wire-end ferrules, Max. wire cross-section: 1 mm², Length: 19 mm, Length of copper pipe: 12 mm, Colour: Red

### Business data

| | |
|---|---|
| Article number | 2796.0 |
| Article name | HZL/1,0 HL-D RD |
| GTIN (EAN) | 4044211055257 |
| Packaging unit | 500 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.17 g |
| Weight per piece (including packaging) | 0.18 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Ferrules |
| Colour | Red |

# Data sheet

## 2796.0 HZL/1,0 HL-D RD

## Technical data

| | |
|---|---|
| **Dimensions** | |
| Length | 19 mm |
| Length of copper pipe | 12 mm |
| Width of plastic collar | 3.2 mm |
| Height of plastic collar | 5.8 mm |
| Diameter of copper pipe | 2 mm |
| Wall thickness of copper pipe | 0.15 mm |
| Wall thickness of plastic collar | 0.3 mm |
| **Connection data** | |
| Wire cross-section, max. | 1 mm² |
| Wire cross-section AWG, max. | 17 |
| Stripping length | 16 mm |
| 2-wire plastic collar | ✓ |
| **Materials** | |
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |
| **Further technical data** | |
| Insulation available | ✓ |
| **Environmental Product Compliance** | |
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

# Data sheet

## 2796.0 HZL/1,0 HL-D RD

## Approvals

### Standards and regulations

| | |
|---|---|
| DIN 46228-4:1990 | yes |

# Data sheet

## 2796.0 HZL/1,0 HL-D RD

## Media

# Data sheet

## 2796.0 HZL/1,0 HL-D RD

## Accessories