# PTV 6 RD - Feed-through terminal block

1291904

https://www.phoenixcontact.com/us/products/1291904

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Feed-through terminal block, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 2, number of positions: 1, connection method: Push-in connection, Rated cross section: 6 $mm^2$, cross section: 0.5 $mm^2$ - 10 $mm^2$, mounting type: NS 35/7,5, NS 35/15, color: red

## Your advantages

- Clear wiring, thanks to lateral conductor entry
- The compact design enables wiring in a confined space
- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system
- In addition to the testing option in the double function shaft, all terminal blocks provide an additional test pick-off

## Commercial data

| | |
|---|---|
| Item number | 1291904 |
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales key | BE23 |
| Product key | BE2311 |
| GTIN | 4063151524258 |
| Weight per piece (including packing) | 14.606 g |
| Weight per piece (excluding packing) | 14.606 g |
| Customs tariff number | 85369010 |
| Country of origin | CN |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Feed-through terminal block |
| Product family | PTV |
| Area of application | Railway industry |
| | Machine building |
| | Plant engineering |
| | Process industry |
| Number of positions | 1 |
| Number of connections | 2 |
| Number of rows | 1 |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Degree of pollution | 3 |

## Electrical properties

| | |
|---|---|
| Rated surge voltage | 8 kV |
| Maximum power dissipation for nominal condition | 1.31 W |

## Connection data

| | |
|---|---|
| Number of connections per level | 2 |
| Nominal cross section | 6 mm² |
| Stripping length | 10 mm ... 12 mm |
| Internal cylindrical gage | A5 |
| Connection in acc. with standard | IEC 60947-7-1 |
| Conductor cross section rigid | 0.5 mm² ... 10 mm² |
| Cross section AWG | 20 ... 8 (converted acc. to IEC) |
| Conductor cross section flexible | 0.5 mm² ... 10 mm² |
| Conductor cross section, flexible [AWG] | 20 ... 8 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.5 mm² ... 6 mm² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.5 mm² ... 6 mm² |
| Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) | 0.5 mm² ... 4 mm² |
| Nominal current | 41 A |
| Maximum load current | 52 A (with 10 mm² conductor cross section, rigid) |
| Nominal voltage | 1000 V |
| Nominal cross section | 6 mm² |

Connection cross sections directly pluggable

| | |
|---|---|
| Conductor cross section rigid | 1.5 mm² ... 10 mm² |
| Conductor cross section, rigid [AWG] | 16 ... 8 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 4 mm² ... 6 mm² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 2.5 mm² ... 6 mm² |

## Ex data

Rated data (ATEX/IECEx)

| | |
|---|---|
| Identification | Ⓔx II 2 G Ex eb IIC Gb |
| Operating temperature range | -60 °C ... 110 °C |
| Ex-certified accessories | 1180894 D-PTV 6 |
| | 3022276 CLIPFIX 35-5 |
| | 1212602 SZS 0,6X3,5 VDE |
| List of bridges | Plug-in bridge / FBS 2-8 / 3030284 |
| | Plug-in bridge / FBS 3-8 / 3030297 |
| | Plug-in bridge / FBS 4-8 / 3030307 |
| | Plug-in bridge / FBS 5-8 / 3030310 |
| | Plug-in bridge / FBS 6-8 / 3032470 |
| | Plug-in bridge / FBS 10-8 / 3030323 |
| Bridge data | 36 A / 6 mm² |
| Ex temperature increase | 40 K (35 A/6 mm²) |
| Rated voltage | 550 V |
| for bridging with bridge | 550 V |
| - At bridging between non-adjacent terminal blocks | 352 V |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 352 V |
| - At cut-to-length bridging | 220 V |
| - At cut-to-length bridging with cover | 275 V |
| Rated insulation voltage | 500 V |
| output | (Permanent) |

Ex level General

| | |
|---|---|
| Rated current | 35 A (6 mm²) |
| Maximum load current | 45 A (10 mm²) |
| Contact resistance | 0.5 mΩ |

Ex connection data General

| | |
|---|---|
| Nominal cross section | 6 mm² |
| Rated cross section AWG | 10 |
| Connection capacity rigid | 0.5 mm² ... 10 mm² |
| Connection capacity AWG | 20 ... 8 |
| Connection capacity flexible | 0.5 mm² ... 10 mm² |
| Connection capacity AWG | 20 ... 8 |

## Dimensions

| | |
|---|---|
| Width | 8.2 mm |
| End cover width | 2.2 mm |
| Height | 61 mm |
| Depth | 42.2 mm |
| Depth on NS 35/7,5 | 43.5 mm |

| | |
|---|---|
| Depth on NS 35/15 | 51 mm |

## Material specifications

| | |
|---|---|
| Color | red |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |
| Insulating material | PA 6.6 |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 125 °C |

## Electrical tests

### Surge voltage test

| | |
|---|---|
| Test voltage setpoint | 8 kV |
| Result | Test passed |

### Temperature-rise test

| | |
|---|---|
| Requirement temperature-rise test | Increase in temperature ≤ 45 K |
| Result | Test passed |
| Short-time withstand current 6 mm² | 0.72 kA |
| Result | Test passed |

### Power-frequency withstand voltage

| | |
|---|---|
| Test voltage setpoint | 2.2 kV |
| Result | Test passed |

## Mechanical properties

### Mechanical data

| | |
|---|---|
| Open side panel | Yes |

## Mechanical tests

### Mechanical strength

| | |
|---|---|
| Result | Test passed |

### Attachment on the carrier

| | |
|---|---|
| DIN rail/fixing support | NS 35 |
| Result | Test passed |

### Test for conductor damage and slackening

| | |
|---|---|
| Rotation speed | 10 rpm |
| Revolutions | 135 |
| Conductor cross section/weight | 0.5 mm² / 0.3 kg |
| | 6 mm² / 1.4 kg |
| | 10 mm² / 2 kg |

| | |
|---|---|
| Result | Test passed |

## Environmental and real-life conditions

### Aging

| | |
|---|---|
| Temperature cycles | 192 |
| Result | Test passed |

### Needle-flame test

| | |
|---|---|
| Time of exposure | 30 s |
| Result | Test passed |

### Oscillation/broadband noise

| | |
|---|---|
| Specification | DIN EN 50155 (VDE 0115-200):2018-05 |
| Spectrum | Service life test category 2, bogie-mounted |
| Frequency | $f_1$ = 5 Hz to $f_2$ = 250 Hz |
| ASD level | 6.12 (m/s²)²/Hz |
| Acceleration | 3.12g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Result | Test passed |

### Shocks

| | |
|---|---|
| Specification | DIN EN 50155 (VDE 0115-200):2018-05 |
| Pulse shape | Half-sine |
| Acceleration | 30g |
| Shock duration | 18 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Result | Test passed |

### Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 90 % |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

## Standards and regulations

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |

## Mounting

| | |
|---|---|
| Mounting type | NS 35/7,5 |
| | NS 35/15 |

## Drawings

Circuit diagram



## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1291904

**IECEE CB Scheme**
Approval ID: DE1-67001

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 1000 V | 41 A | - | 0.5 - 10 |

**EAC**
Approval ID: RU C-DE.BL08.B.00644

**VDE Zeichengenehmigung**
Approval ID: 40056061

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 1000 V | 41 A | - | 0.5 - 10 |

**CCC**
Approval ID: 2021122313114374

**IECEx**
Approval ID: IECExPTB20.0037U

**ATEX**
Approval ID: PTB20ATEX1016U

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC000897 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

## Accessories

Note: Applying some accessories below might limit this product.

### FBS 2-8 - Plug-in bridge

3030284

https://www.phoenixcontact.com/us/products/3030284

Max. current carrying capacity: 41 A

Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

### FBS 3-8 - Plug-in bridge

3030297

https://www.phoenixcontact.com/us/products/3030297

Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red

Max. current carrying capacity: 41 A

## FBS 4-8 - Plug-in bridge

3030307

https://www.phoenixcontact.com/us/products/3030307

Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red

Max. current carrying capacity: 41 A

## FBS 5-8 - Plug-in bridge

3030310

https://www.phoenixcontact.com/us/products/3030310

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red

Max. current carrying capacity: 41 A

## FBS 6-8 - Plug-in bridge

3032470

https://www.phoenixcontact.com/us/products/3032470

Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: red

Max. current carrying capacity: 41 A

## FBS 10-8 - Plug-in bridge

3030323

https://www.phoenixcontact.com/us/products/3030323

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

Max. current carrying capacity: 41 A

## FBS 2-8 CT - Plug-in bridge

3033830

https://www.phoenixcontact.com/us/products/3033830

Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: orange

Max. current carrying capacity: 41 A

## FBS 3-8 CT - Plug-in bridge

3033831

https://www.phoenixcontact.com/us/products/3033831

Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: orange

Max. current carrying capacity: 41 A

## FBS 4-8 CT - Plug-in bridge

3033832

https://www.phoenixcontact.com/us/products/3033832

Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: orange

Max. current carrying capacity: 41 A

## FBS 10-8 CT - Plug-in bridge

3033833

https://www.phoenixcontact.com/us/products/3033833

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: orange

Max. current carrying capacity: 41 A

## FBS 2-8 BU - Plug-in bridge

3032567

https://www.phoenixcontact.com/us/products/3032567

Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: blue

Max. current carrying capacity: 41 A

## FBS 3-8 BU - Plug-in bridge

3032570

https://www.phoenixcontact.com/us/products/3032570

Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: blue

Max. current carrying capacity: 41 A

## FBS 4-8 BU - Plug-in bridge

3032583

https://www.phoenixcontact.com/us/products/3032583

Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: blue

Max. current carrying capacity: 41 A

## FBS 5-8 BU - Plug-in bridge

3032596

https://www.phoenixcontact.com/us/products/3032596

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: blue

Max. current carrying capacity: 41 A

## FBS 6-8 BU - Plug-in bridge

3032677

https://www.phoenixcontact.com/us/products/3032677

Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: blue

Max. current carrying capacity: 41 A

## FBS 10-8 BU - Plug-in bridge

3032606

https://www.phoenixcontact.com/us/products/3032606

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: blue

Max. current carrying capacity: 41 A

## FBS 2-8 GY - Plug-in bridge

3032621

https://www.phoenixcontact.com/us/products/3032621

Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: gray

Max. current carrying capacity: 41 A

## FBS 3-8 GY - Plug-in bridge

3032622

https://www.phoenixcontact.com/us/products/3032622

Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: gray

Max. current carrying capacity: 41 A

## FBS 4-8 GY - Plug-in bridge

3032635

https://www.phoenixcontact.com/us/products/3032635

Max. current carrying capacity: 41 A

Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: gray

## FBS 5-8 GY - Plug-in bridge

3032648

https://www.phoenixcontact.com/us/products/3032648

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: gray

Max. current carrying capacity: 41 A

## FBS 6-8 GY - Plug-in bridge

3032664

https://www.phoenixcontact.com/us/products/3032664

Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: gray

Max. current carrying capacity: 41 A

## FBS 10-8 GY - Plug-in bridge

3032651

https://www.phoenixcontact.com/us/products/3032651

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: gray

Max. current carrying capacity: 41 A

## FBS 1/4/7/10-8 - Plug-in bridge

3032402

https://www.phoenixcontact.com/us/products/3032402

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, pin assignment: 1,4,7,10, color: red

Max. current carrying capacity: 41 A

## FBS 1/3/5-8 - Plug-in bridge

3032389

https://www.phoenixcontact.com/us/products/3032389

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, pin assignment: 1,3,5, color: red

Max. current carrying capacity: 41 A

## FBS 1/5-8 - Plug-in bridge

3032381

https://www.phoenixcontact.com/us/products/3032381

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, pin assignment: 1,5, color: red

Max. current carrying capacity: 41 A

## FBS 1/3-8 - Plug-in bridge

3032363

https://www.phoenixcontact.com/us/products/3032363

Plug-in bridge, pitch: 8.2 mm, number of positions: 3, pin assignment: 1,3, color: red

Max. current carrying capacity: 41 A

## FBSR  5-8 - Plug-in bridge

3033809

https://www.phoenixcontact.com/us/products/3033809

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red

Max. current carrying capacity: 32 A

## FBSR 10-8 - Plug-in bridge

3001599

https://www.phoenixcontact.com/us/products/3001599

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

Max. current carrying capacity: 32 A

## FBSR 16-8 - Plug-in bridge

3033816

https://www.phoenixcontact.com/us/products/3033816



Plug-in bridge, pitch: 8.2 mm, number of positions: 16, color: red

Max. current carrying capacity: 32 A

## RB ST 6-(2,5/4) - Reducing bridge

3030860

https://www.phoenixcontact.com/us/products/3030860

Reducing bridge, pitch: 9 mm, number of positions: 2, length: 30 mm, color: red

Max. current carrying capacity: 35 A

## RB 16-6 - Reducing bridge

3047072

https://www.phoenixcontact.com/us/products/3047072

Max. current carrying capacity: 37 A

Reducing bridge, pitch: 12.2 mm, number of positions: 2, color: red

## RB ST 6-1,5/S - Reducing bridge

3213250

https://www.phoenixcontact.com/us/products/3213250

Reducing bridge, pitch: 8 mm, number of positions: 2, length: 30 mm, color: red

Max. current carrying capacity: 24 A

## D-PTV 6 - Cover

1180894

https://www.phoenixcontact.com/us/products/1180894

Cover, depth: 36 mm, width: 2.2 mm, height: 61 mm, color: gray

## WS PT 6 - Warning label

1029029

https://www.phoenixcontact.com/us/products/1029029

Warning label, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 8.2 mm

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

https://www.phoenixcontact.com/us/products/0801733

DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

https://www.phoenixcontact.com/us/products/0801681

DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

https://www.phoenixcontact.com/us/products/1204119

DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

https://www.phoenixcontact.com/us/products/1204122

DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

https://www.phoenixcontact.com/us/products/0801704

DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

https://www.phoenixcontact.com/us/products/1206421

DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

https://www.phoenixcontact.com/us/products/1206434

DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

https://www.phoenixcontact.com/us/products/0801762

DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## NS 35/ 7,5 CAP - End cap

1206560

https://www.phoenixcontact.com/us/products/1206560

DIN rail end piece, for DIN rail NS 35/7.5

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

https://www.phoenixcontact.com/us/products/1201730

DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

https://www.phoenixcontact.com/us/products/1201714

DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

https://www.phoenixcontact.com/us/products/0806602

DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

https://www.phoenixcontact.com/us/products/1204135

DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

https://www.phoenixcontact.com/us/products/1201756

DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

https://www.phoenixcontact.com/us/products/1206599

DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

https://www.phoenixcontact.com/us/products/1206586

DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

https://www.phoenixcontact.com/us/products/1201895

DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## NS 35/15 CAP - End cap

1206573

https://www.phoenixcontact.com/us/products/1206573

DIN rail end piece, for DIN rail NS 35/15

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

https://www.phoenixcontact.com/us/products/1201798

DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

## ZB 8:UNBEDRUCKT - Zack marker strip

1052002

https://www.phoenixcontact.com/us/products/1052002

Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

## ZB 8 CUS - Zack marker strip

0825011

https://www.phoenixcontact.com/us/products/0825011

Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

## UC-TM 8 - Marker for terminal blocks

0818072

https://www.phoenixcontact.com/us/products/0818072

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

## UC-TM 8 CUS - Marker for terminal blocks

0824597

https://www.phoenixcontact.com/us/products/0824597

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

## UCT-TM 8 - Marker for terminal blocks

0828740

https://www.phoenixcontact.com/us/products/0828740

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

## UCT-TM 8 CUS - Marker for terminal blocks

0829616

https://www.phoenixcontact.com/us/products/0829616

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

## ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

https://www.phoenixcontact.com/us/products/1052015

Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10

## ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

https://www.phoenixcontact.com/us/products/1052028

Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10

## ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

https://www.phoenixcontact.com/us/products/1052413

Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

## ZBF 8:UNBEDRUCKT - Zack Marker strip, flat

0808781

https://www.phoenixcontact.com/us/products/0808781

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

## ZBF 8 CUS - Zack Marker strip, flat

0825030

https://www.phoenixcontact.com/us/products/0825030

Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

## ZBF 8,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808804

https://www.phoenixcontact.com/us/products/0808804

Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 101 ... 110, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

## UC-TMF 8 - Marker for terminal blocks

0818137

https://www.phoenixcontact.com/us/products/0818137

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

## UC-TMF 8 CUS - Marker for terminal blocks

0824654

https://www.phoenixcontact.com/us/products/0824654

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

## UCT-TMF 8 - Marker for terminal blocks

0828748

https://www.phoenixcontact.com/us/products/0828748

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

## UCT-TMF 8 CUS - Marker for terminal blocks

0829672

https://www.phoenixcontact.com/us/products/0829672

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

## MPS-MT - Test plug

0201744

https://www.phoenixcontact.com/us/products/0201744

Test plug, with solder connection up to 1 $mm^2$ conductor cross section, number of positions: 1, color: gray

## MPS-IH WH - Insulating sleeve

0201663

https://www.phoenixcontact.com/us/products/0201663

Insulating sleeve, color: white

## MPS-IH RD - Insulating sleeve

0201676

https://www.phoenixcontact.com/us/products/0201676

Insulating sleeve, color: red

## MPS-IH BU - Insulating sleeve

0201689

https://www.phoenixcontact.com/us/products/0201689

Insulating sleeve, color: blue

## MPS-IH YE - Insulating sleeve

0201692

https://www.phoenixcontact.com/us/products/0201692

Insulating sleeve, color: yellow

## MPS-IH GN - Insulating sleeve

0201702

https://www.phoenixcontact.com/us/products/0201702

Insulating sleeve, color: green

## MPS-IH GY - Insulating sleeve

0201728

https://www.phoenixcontact.com/us/products/0201728

Insulating sleeve, color: gray

## MPS-IH BK - Insulating sleeve

0201731

https://www.phoenixcontact.com/us/products/0201731

Insulating sleeve, color: black

## PAI-4-FIX BU - Test adapter

3032729

https://www.phoenixcontact.com/us/products/3032729

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: blue

## PAI-4-FIX OG - Test adapter

3034455

https://www.phoenixcontact.com/us/products/3034455

4 mm test adapter, for terminal blocks with 8.2 mm pitch

## PAI-4-FIX YE - Test adapter

3032745

https://www.phoenixcontact.com/us/products/3032745

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: yellow

## PAI-4-FIX RD - Test adapter

3032732

https://www.phoenixcontact.com/us/products/3032732

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: red

## PAI-4-FIX GN - Test adapter

3032758

https://www.phoenixcontact.com/us/products/3032758

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: green

## PAI-4-FIX BK - Test adapter

3032774

https://www.phoenixcontact.com/us/products/3032774

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: black

## PAI-4-FIX GY - Test adapter

3032790

https://www.phoenixcontact.com/us/products/3032790

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: gray

## PAI-4-FIX VT - Test adapter

3032761

https://www.phoenixcontact.com/us/products/3032761

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: violet

## PAI-4-FIX BN - Test adapter

3032787

https://www.phoenixcontact.com/us/products/3032787

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: brown

## PAI-4-FIX WH - Test adapter

3032797

https://www.phoenixcontact.com/us/products/3032797

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: white

## PAIS-4-FIX GY - Test adapter

3032791

https://www.phoenixcontact.com/us/products/3032791

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: gray

## PAIS-4-FIX BK - Test adapter

3032792

https://www.phoenixcontact.com/us/products/3032792

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: black

## PAIS-4-FIX RD - Test adapter

3032793

https://www.phoenixcontact.com/us/products/3032793

Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: red

## PAIS-4-FIX BU - Test adapter

3032798

https://www.phoenixcontact.com/us/products/3032798

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: blue

## PAIS-4-FIX YE - Test adapter

3032799

https://www.phoenixcontact.com/us/products/3032799

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: yellow

## PAIS-4-FIX GN - Test adapter

3032801

https://www.phoenixcontact.com/us/products/3032801

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: green

## PAIS-4-FIX VT - Test adapter

3032802

https://www.phoenixcontact.com/us/products/3032802

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: violet

## PS-8 - Test plug

3031005

https://www.phoenixcontact.com/us/products/3031005

Test plug, Modular test plug, number of positions: 1, color: red

## DP PS-8 - Spacer plate

3036741

https://www.phoenixcontact.com/us/products/3036741

Spacer plate, depth: 29 mm, width: 8.2 mm, height: 22.4 mm, number of positions: 1, color: red

## PS-8/2,3MM RD - Test plug

3048564

https://www.phoenixcontact.com/us/products/3048564

Test plug, number of positions: 1, color: red

## SZK PH0 VDE - Screwdriver

1205147

https://www.phoenixcontact.com/us/products/1205147

Screwdriver, PH crosshead, VDE insulated, size: PH 0 x 80 mm, 2-component grip, with non-slip grip

## SZK PH1 VDE - Screwdriver

1205150

https://www.phoenixcontact.com/us/products/1205150

Screwdriver, PH crosshead, VDE insulated, size: PH 1 x 80 mm, 2-component grip, with non-slip grip

## SZK PH2 VDE - Screwdriver

1205163

https://www.phoenixcontact.com/us/products/1205163

Screwdriver, PH crosshead, VDE insulated, size: PH 2 x 100 mm, 2-component grip, with non-slip grip

## SZK PZ0 VDE - Screwdriver

1206447

https://www.phoenixcontact.com/us/products/1206447

Screwdriver, PZ crosshead, VDE insulated, size: PZ 0 x 80 mm, 2-component grip, with non-slip grip

## SZK PZ1 VDE - Screwdriver

1206450

https://www.phoenixcontact.com/us/products/1206450

Screwdriver, PZ crosshead, VDE insulated, size: PZ 1 x 80 mm, 2-component grip, with non-slip grip

## SZK PZ2 VDE - Screwdriver

1206463

https://www.phoenixcontact.com/us/products/1206463

Screwdriver, PZ crosshead, VDE insulated, size: PZ 2 x 100 mm, 2-component grip, with non-slip grip

## SZS 0,6X3,5 VDE - Screwdriver

1212602

https://www.phoenixcontact.com/us/products/1212602

Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

## SZS 0,8X4,0 VDE - Screwdriver

1212508

https://www.phoenixcontact.com/us/products/1212508

Screwdriver, slot-headed, VDE insulated, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

## SZS 1,0X4,0 VDE - Screwdriver

1205066

https://www.phoenixcontact.com/us/products/1205066

Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

## SZS 1,0X5,5 VDE - Screwdriver

1209114

https://www.phoenixcontact.com/us/products/1209114

Screwdriver, slot-headed, VDE insulated, size: 1.0 x 5.5 x 125 mm, 2-component grip, with non-slip grip

## SZS 1,0X6,5 VDE - Screwdriver

1205079

https://www.phoenixcontact.com/us/products/1205079

Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

## PROJECT COMPLETE - Software

1050453

https://www.phoenixcontact.com/us/products/1050453

Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com