BeanAir IOT

STARTERKIT

Wireless IOT Data Acquisition(DAQ) Instrument
Analog voltage inputs ±10V



BeanScape® 2.4GHz VERSION

PRODUCT VIDEO

USER GUIDE

QUICK START

REFERENCE SK-WIRELESS-DAQ-ANV-10-IND

DESCRIPTION

Get Started Instantly with Our Wireless DAQ (for analog sensors ±10V) Starter Kit :

- Wireless Receiver/Gateway + LAN Output + Indoor version IP40 (Ref: BGTW-2.4GHZ-ETH-IND)
- Wireless DAQ for analog sensors ±10V (REF: BND-2.4GHZ-ANV-10-4CH)
- 1 x Free software to collect and display in real-time data measurement (Ref: BNSC-2.4GHZ-LITE)
- AC/DC Power Adapter (US or EUR or UK plugs*) for charging the battery or to be used constantly

BeanAir IOT STARTERKIT

Wireless IOT Data Acquisition(DAQ) Instrument
Analog voltage inputs ±10V


MAIN FEATURES

- Analog inputs ±10V (4 channels)
- Measurement precision less than ± 0.01% on the full scale
- Integrated sensor power supply, software configurable 4.5V to 20V (i.e. no need external power for your sensors)
- Global License-free band 2.4GHZ, with maximum radio range 650 meters (can be extended to 1km with higher gain antenna)
- Waterproof and rugged IP67 aluminum casing (Nema 6)
- Time-synchronized data acquisition (±2.5ms of accuracy)
- Rechargeable Lithium-Polymer battery 2200 mAh providing a battery life up to 12 months
- Embedded data logger : up to 1 million data points with events dating

This Wireles DAQ system is suitable for industrial sensors with current-loop outputs.

Beanair products are Made in Germany and are certified CE/FCC/Giteki


HOW IT WORKS ?



WEBLINKS TO PRODUCTS

- Wireless DAQ system
- Wireless Receiver/Gateway
- Eco-friendly Monitoring Software

DRAWING



CONTACT US

Headquarter:
Buchholzer Straße 65, 13156
Berlin, Germany

Email:
info@beanair.com

Phone number:
+493066405051