



Data sheet | Item number: 787-2805
DC/DC Converter; 24 VDC input voltage; 12 VDC output voltage; 0.5 A
output current; DC OK contact



www.wago.com/787-2805



DC O.K.	1	5	n.c.
GND	2	6	n.c.
Vout+	3	7	Vin+
GND	4	8	GND



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Features:

- DC/DC converter in a compact 6 mm housing
- DC/DC converters (787-28xx) supply devices with 5, 10, 12 or 24 VDC from a 24 or 48 VDC power supply with an output power up to 12 W.
- Output voltage monitoring via DC OK signal output
- Can be commoned with 857 and 2857 Series devices
- Comprehensive range of approvals for multiple applications

Data

Technical data

Input

Nominal input voltage $U_{i \text{ nom}}$	DC 24 V
Input voltage range	DC 15 ... 30 V
Nominal mains frequency range	0 Hz
Input current I_i	$\leq 0.5 \text{ A}$
Inrush current	$\leq 0.5 \text{ A}$ (at nominal input voltage)

Output

Nominal output voltage $U_{o \text{ nom}}$	DC 12 V
Output voltage range	$\pm 2 \%$
Nominal output current $I_{o \text{ nom}}$	0.5 A
Nominal output power	6 W
Deviation	$\leq 2 \%$
Residual ripple	$\leq 20 \text{ mV}$ (peak-to-peak)

Signaling and communication

Signaling	1 x LED DC OK (green) 1 x Short circuit LED (red) 1 x Active signal output (U_i , max. 4 mA)
Operation status indicator	Green LED (U_o) Red LED (short circuit)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Efficiency/power losses

Power loss P_l	$\leq 0.21 \text{ W}; \leq 0.7 \text{ W}$ (nominal load)
Efficiency (typ.)	90 % (at nominal input voltage and nominal output)

Circuit protection

Internal fuse	No
---------------	----

Safety and protection

Protection class	III
Protection type	IP20; per EN 60529
Reverse voltage protection	yes
Pollution degree	2
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	No
Series operation	No
MTBF	> 1,800,000 h

Connection data

Number of jumper slots	8
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 857 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.34 ... 2.5 mm ² / 22 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	6 mm / 0.236 inches
Height	94 mm / 3.701 inches
Depth from upper-edge of DIN-rail	97.8 mm / 3.85 inches

Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Material data

Fire load	0.363 MJ
Weight	48.6 g

Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	95% (no condensation permissible)
Derating	No derating
Climatic category	3K3 (per EN 60721; except for low air pressure)

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61000-6-2 EN 61000-6-3 EN 60950-1 UL 61010-2-201

Commercial data

eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 8.0	EC002540
ETIM 7.0	EC002540
ECCN	NO DATA
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	DE
GTIN	4055143407045
Customs tariff number	85044083900

Environmental Product Compliance

CAS-No.	11120-22-2 1303-86-2 1317-36-8 7439-92-1
REACH Candidate List Substance	Diboron trioxide Lead

Subject to changes. Please also observe the further product documentation!



	Lead monoxide Lead silicate
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	4f2a43e4-a730-4da6-863a-5a38b11c0458
SCIP notification number (Belgium)	f9285629-a82b-482e-9934-56caaa89bd90
SCIP notification number (Bulgaria)	aa1c2089-ca90-475b-b065-b290f8c47c73
SCIP notification number (Czech Republic)	e4407a61-44ef-46f6-8b71-5957fb1b0e35
SCIP notification number (Denmark)	62e3f530-0083-4301-a58f-c18079aaac67
SCIP notification number (Finland)	b5859d05-b7e1-4a35-a43a-cf33af17f955
SCIP notification number (France)	9a8251e6-a882-4123-987f-3af679ef6e75
SCIP notification number (Germany)	6edaf339-2ec1-4a85-bfcf-c4ac37d4e41b
SCIP notification number (Hungary)	50511142-efbe-4d96-bb7d-4eb00b7c1b98
SCIP notification number (Italy)	7c3519fd-876f-4af4-a334-e0f41b17ffce
SCIP notification number (Netherlands)	f84285ba-e8f4-418f-8037-d27c744e1818
SCIP notification number (Poland)	91abfe2e-594d-4cbf-9277-a9a191349087
SCIP notification number (Romania)	a5085aab-1513-44f7-a544-88b3170333b2
SCIP notification number (Sweden)	7ecaaaff-70ab-45de-8e2c-ff4a34524af3

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199 Vol3 Sec1

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Optional accessories

Tool

Operating tool



Item no.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

www.wago.com/210-720

Marking accessories

Marking strip



Item no.: 2009-110

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

www.wago.com/2009-110

Marker



Item no.: 2009-115

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

www.wago.com/2009-115



Item no.: 793-501

WMB marking card; as card; not stretchable; plain; snap-on type; white

www.wago.com/793-501



Item no.: 793-502

WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-502



Item no.: 793-503

WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-503



Item no.: 793-504

WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-504



Item no.: 793-505

WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-505



Item no.: 793-506

WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-506



Item no.: 793-566

WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white

www.wago.com/793-566

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Item no.: 793-5501

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white

www.wago.com/793-5501

Downloads

Documentation

Bid Text

787-2805 X81 - Datei	19 февр. 2019 г.	xml 5.8 kB	Download
-------------------------	------------------	---------------	----------

787-2805 doc - Datei	11 янв. 2016 г.	doc 35.3 kB	Download
-------------------------	-----------------	----------------	----------

787-2805 pdf - Datei	11 янв. 2016 г.	pdf 91.9 kB	Download
-------------------------	-----------------	----------------	----------

787-2805 docx - Datei	11 янв. 2016 г.	docx 20.4 kB	Download
--------------------------	-----------------	-----------------	----------

Instruction Leaflet

DC/DC-Wandler	V 1.1.1 31 мар. 2020 г.	pdf 2.4 MB	Download
---------------	----------------------------	---------------	----------

Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 18 авг. 2022 г.	pdf 2.2 MB	Download
---	----------------------------	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 787-2805	URL	Download
-----------------------	-----	----------

CAE data

EPLAN Data Portal 787-2805	URL	Download
----------------------------	-----	----------

WSCAD Universe 787-2805	URL	Download
-------------------------	-----	----------

ZUKEN Portal 787-2805	URL	Download
-----------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



Asset Administration Shell

Asset Administration Shell 787-2805	URL	Download
-------------------------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-2805	URL	Download
DC/DC Converter; 24 VDC input voltage; 12 VDC output voltage; 0.5 A output current; DC OK contact		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.