

# BC-M12M4x-22-x 4-pin Single-Ended Male Cordsets



## Features

- M12 male to flying leads, four conductors, multiple length options
- Black PVC jacket, unshielded, A-code connector
- Straight and right-angle connector options

## BC-M12M4-22-X Models

4-pin M12 Cordsets - Male Single-Ended, Straight				
Model	Length	Dimensions (mm)	Pinout (Male)	
BC-M12M4-22-1	1 m (3.28 ft)			1 = Brown 2 = White 3 = Blue 4 = Black
BC-M12M4-22-2	2 m (6.56 ft)			
BC-M12M4-22-5	5 m (16.4 ft)			
BC-M12M4-22-8	8 m (26.25 ft)			
BC-M12M4-22-10	10 m (30.81 ft)			
BC-M12M4-22-15	15 m (49.2 ft)			
4-pin M12 Cordsets - Male Single-Ended, Right-Angle				
Model	Length	Dimensions (mm)	Pinout (Male)	
BC-M12M4A-22-1	1 m (3.28 ft)			1 = Brown 2 = White 3 = Blue 4 = Black
BC-M12M4A-22-2	2 m (6.56 ft)			
BC-M12M4A-22-5	5 m (16.4 ft)			
BC-M12M4A-22-8	8 m (26.25 ft)			
BC-M12M4A-22-10	10 m (30.81 ft)			
BC-M12M4A-22-15	15 m (49.2 ft)			

## BC-M12M4-22-X Specifications

### Current Rating

4 A

### Voltage Rating

250 V

### Minimum Bend Radius

Installation:

Static: 5× the outside diameter

Dynamic: 10× the outside diameter

### AWG

22 AWG

### Outer Diameter

5.21 mm

### Coding

A

### Connections

Integral 4-pin M12 male quick disconnect

### Construction

Coupling nut material: Nickel-plated brass

Contact carrier: Black nylon

Connector body: Black PUR

Jacket material: Black PVC

### Operating Conditions

Operating temperature: -40 °C to +70 °C (-40 °F to +158 °F)

Storage temperature: -40 °C to +70 °C (-40 °F to +158 °F)

90% at +50 °C maximum relative humidity (non-condensing)

### Vibration and Mechanical Shock

Meets IEC 60068-2-6 requirements (Vibration: 10 Hz to 55 Hz, 1.0 mm amplitude, 5 minutes sweep, 30 minutes dwell)

Meets IEC 60068-2-27 requirements (Shock: 30G 11 ms duration, half sine wave)

### Environmental Rating

IP66, IP67, IP68

## Banner Engineering Corp Limited Warranty

---

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

**THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.**

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: [www.bannerengineering.com](http://www.bannerengineering.com).

For patent information, see [www.bannerengineering.com/patents](http://www.bannerengineering.com/patents).

Document title: BC-M12M4x-22-x 4-pin Single-Ended Male Cordsets  
Part number: 235940  
Revision: A  
Original Instructions  
© Banner Engineering Corp. All rights reserved.

