

## Han-Fast Lock 10mm<sup>2</sup>, Ag

		Part number	09 08 000 7924
		Specification	Han-Fast Lock 10mm², Ag
Identification			
Category	Contacts		
Series	Han-Fast <sup>®</sup> L		
Type of contact	PCB contact		
Description of the contact	Without pin		
Version			
Pack contents	Single conta	ct	
Technical characteristics			
Conductor cross-section	10 mm <sup>2</sup>		
Rated current	≤60 A		
Contact resistance	≤2 mΩ		
Stripping length	7.5 mm		
Material properties			
Material (contacts)	Copper alloy	,	
Surface (contacts)	Silver plated		
Material (locking)	Copper alloy	,	
Surface (locking)	Passivated		
RoHS	compliant		
ELV status	compliant		
China RoHS	е		
REACH Annex XVII substances	Not containe	d	
REACH ANNEX XIV substances	Not containe	d	

Page 1 / 2 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
Specifications and approvals	
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Commercial data	
Packaging size	1
Net weight	1.08 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140014909
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)