




Type GF-P-LS



Product information

The self-retracting fabric conduit with longitudinal slot provides excellent mechanical protection against abrasion for your lines. First off it prevents rattling even better, plus it can be installed at any place and at any time.

Additional advantages of the GF-P-LS braided conduit include:

- High mechanical protection
- Light-weight / low mass
- High flexibility
- Great chemical resistance
- Flame resistant

Specification:

- EN 45545-2 2x HL3 1X HL2

Color: Black

UV: 1

PU m: 25

Information, conformities and approvals



Article	Order No.	Nominal widths NW	Size range mm	Weight kg/100m
GF-P-LS-5	83342110	5	3 / 5	1.71
GF-P-LS-8	83342112	8	5 / 8	2.12
GF-P-LS-10	83342114	10	8 / 10	2.43
GF-P-LS-13	83342116	13	10 / 13	2.54
GF-P-LS-16	83342118	16	13 / 16	3.38
GF-P-LS-19	83342120	19	16 / 19	3.38
GF-P-LS-25 ¹⁾	83342122	25	22 / 25	4.81
GF-P-LS-29	83342124	29	26 / 29	5.18
GF-P-LS-32	83342126	32	29 / 32	6.35
GF-P-LS-38	83342128	38	32 / 44	7.56



Type GF-P-LS

Article	Order No.	Nominal widths NW	Size range mm	Weight kg/100m
GF-P-LS-50	83342130	50	44 / 50	7.56
¹) No stock goods, delivery time and minimum order quantities upon request				

Material properties



mod. polyester

Thermal properties



Temperature / temperature range -55 °C – 150 °C
short termshort term: 175 °C

Fire properties



Fire classification UL 224 / FMV
SS302 self-extinguishing type B



Fire properties as per EN 45545-2 C.I.T. R22 / R23 HL3 ; LOI
R22 / R23 HL3 ; Ds (max.) R22 HL2 / R23 HL3 : 0,11, 34.0, 213

Technical information



Halogen-free

Conformity



RoHS (EC Directive
2011/65/EU)

Approvals and operating permits



EU railway approval