

CyberPower

B625 | ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Essential Surge Protector B625 from CyberPower offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The B625 provides 1500 joules of protection with six outlets and a long, 25-foot power cord.

Features of the B625 include automatic shutdown, metal oxide varistor (MOV) technology, 25-foot power cord, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 1500 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5 to 15P
- Plug style: Right-angle 45° offset
- Outlet type: 6 NEMA 5 to 15R (surge-protected)
- Power cord: 25 ft.
- Model color: White
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$150,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	25 ft. (7.6 m)
Input Plug Type	NEMA 5 to 15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	6 NEMA 5 to 15R
Outlets - Total	6

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	600V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz / 100 MHz / Yes
Maximum Surge Current	45,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,500 J

B625

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS - CONTINUED

PHYSICAL	
Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.55 cm, 3.81 cm, 24.79 cm
Physical Dimensions - Width/Height/Depth (mm)	45 mm, 38 mm, 248 mm
Physical Dimensions - Width/Height/Depth (in.)	1.79 in., 1.5 in., 9.76 in.
Weight (kg)	1.12 kg
Weight (lbs.)	2.46 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	16.51 cm, 35.51 cm, 9.5 cm
Shipping Dimensions - Width/Height/Depth (mm)	165.1 mm, 355.09 mm, 95 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.5 in., 13.98 in., 3.74 in.
Shipping Weight (kg)	1.24 kg
Shipping Weight (lbs.)	2.74 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 3rd Edition cUL

WARRANTY	
CEG Amount	\$150,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime